


# Dial Bore Gauges

## ***Quick and Accurate Measuring of Injection & Extrusion Cylinder Bores***

**Dial Bore Gauges** allow rapid and accurate checking of bores for size, ovality, taper, wear, etc. All models operate on the proven principle of two diametrically opposed measuring points, one fixed and one moving, plus a spring-loaded centralizing shoe.

PART NO.	BORE CAPACITY	IN REACH	PRICE EACH
PSE21010-12	7/8" - 2"	12"	CALL
PSE21010-18	7/8" - 2"	18"	\$1095.00
PSE21010-24	7/8" - 2"	24"	CALL
PSE21010-36	7/8" - 2"	36"	CALL
PSE21010-48	7/8" - 2-1/2"	48"	\$1450.00
PSE21010-72	7/8" - 2-1/2"	72"	\$1750.00
PSE21510-12	2" - 6"	12"	CALL
PSE21510-18	2" - 6"	18"	\$1095.00
PSE21510-24	2" - 6"	24"	CALL
PSE21510-36	2" - 6"	36"	CALL
PSE21510-48	2" - 6"	48"	\$1450.00
PSE21510-60	2" - 6"	60"	CALL
PSE21510-72	2" - 6"	72"	\$1750.00
PSE21510-84	2" - 6"	84"	CALL
PSE21510-96	2" - 6"	96"	\$1995.00
PSE23510-	6" - 24"	--	CALL

*Additional Lengths Quoted on Request.  
\*Maximum Length Available is 96"*



To check the actual size of a bore, the gauge must be set to size with a bore of a known diameter, or by means of a micrometer measurement over the fixed and moving points. Inserted into the bore, it is only necessary to "rock" the gauge slowly to locate its measuring axis to the bore, shown by the point of reversal of the indicator hand. The reading at that point is the deviation from set or normal size. A range of interchangeable extension rods allow a single instrument to cover a wide range of bore sizes.

### **BENEFITS:**

- Reduce Lost Profits Due to Worn Barrels
- Simple to Operate
- Measure at Your Convenience; Not a Service Tech's


### **FEATURES:**

- No Electric or Air Hookup Needed
- .0005 Graduation Indicator Readings
- Built-in Centralizer Shoe for Easy Repetitive Performance
- Shock Protected Movements with Revolution Counter

CALL TODAY FOR MORE  
INFORMATION ON

**BORE GAUGES**

**800-627-1033**



***Metric Gauges Also Available***