

Lubricants and Penetrants



SW077 Industrial Silicone Lubricant

SW077 stops sticking and retards corrosion. This silicone spray eliminates annoying squeaks in hinges, latches, springs, etc. It leaves no greasy or oily film and is not affected by water or oil. The heat stable formula will not freeze or melt.

Packaged twelve 20 fluid ounce (12 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW077	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW090 Industrial RD 90

SW090 provides a fine film coating that keeps moving parts and operating mechanisms running smoothly while it displaces moisture and prevents rust on any metal. This product contains no silicone and is harmless to paint, plastic, rubber and fabric. Spray on corroded and rusted "frozen" parts for quick release.

Packaged twelve 16 fluid ounce (11 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW090	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW288 L1 Lubricant Protectant

SW288 is designed to work fast loosening rust and corrosion. The non-conductive formula with moisture displacer, never dries. Saves production, maintenance and repair time while protecting and preserving equipment.

Packaged twelve 20 fluid ounce (15 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW288	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW289 L3 Moly PTFE Lubricant Protectant

SW289 is formulated with PTFE and fortified with Moly to provide long lasting lubrication and protection from friction, wear and corrosion. The light viscosity of this product allows for deep penetration into hard to reach moving parts. Safe for use on most surfaces.

Packaged twelve 20 fluid ounce (15 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW289	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase

Lubricants and Penetrants



SW290 Moisture Displacer Deep Penetrant

SW290 protects faster than traditional products. Saves production, maintenance and repair time protecting equipment with its rust inhibitor. This moisture displacer reaches deep down to loosen nuts and bolts where corrosion and rust have collected.

Packaged twelve 20 fluid ounce (20 oz. net weight) cans per case.

CASES AND CANS

PART NO. SW290	
1-11 Cans	Call for Pricing
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW291 M1 Moly Chain & Cable Lubricant

SW291 provides superior penetrating action to rollers, pins, links and bushings of chains. When applied to wire ropes and cables, the Moly and other additives plate the strands to provide anti-wear and rust protection

Packaged twelve 20 fluid ounce (15 oz. net weight) cans per case.

CASES AND CANS

PART NO. SW291	
1-11 Cans	Call for Pricing
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW292 S1 Silicone Spray

SW292 is non-staining, non-corrosive and quick drying for a variety of uses. May be used on equipment in areas where there is incidental exposure of the lubricated parts to food. This friction reducer stops sticking and binding while it protects equipment.

Packaged twelve 20 fluid ounce (11 oz. net weight) cans per case.

CASES AND CANS

PART NO. SW292	
1-11 Cans	Call for Pricing
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW294 G1 Premium Gold Grease

SW294 is a premium gold grease that delivers excellent lubrication while it prevents corrosion and extending of the life of operating equipment. This product is fortified with extreme pressure additives to withstand extreme temperatures and extreme conditions.

Packaged twelve 20 fluid ounce (13 oz. net weight) cans per case.

CASES AND CANS

PART NO. SW294	
1-11 Cans	Call for Pricing
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase

Lubricants and Penetrants



SW295 T1 TFE Dry Coating Lubricant & Release Agent

SW295 is a non-oily, non-staining woodworker's lubricant that remains dry during use. Extremely slick, SW295 will not melt below 500°F, will not attract or hold dust or dirt and will not become gummy. Repels oil and water. Reduces friction. Inhibits resin build-up while it prolongs tool life.

Packaged twelve 20 fluid ounce (12 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW295	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW460 OG Open Gear Lubricant

SW460 is a super-tough, adhesive-type lubricant which penetrates deep into gears, cables and heavy duty mechanisms. Thickens quickly to a tacky, black, stringy lube. Provides a Molybdenum Disulfide shield which maintains a cushion of lubricant between gear teeth and other friction-producing surfaces. Absorbs high shock loads, extreme pressure and prevents chipping and scuffing.

Packaged twelve 20 fluid ounce (14 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW460	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW463 M3 Dry Moly Lubricant

SW463 offers extreme condition, dry, friction reducing lubricant and anti-seize coating. While withstanding high temperatures and extreme pressures. SW463 provides a dry film lubricant especially suited for use in dirty or dusty atmospheres.

Packaged twelve 16 fluid ounce (12 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW463	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW464 M2 Dry Moly Lubricant

SW464 is a dry lubricant that can be used for extreme temperatures ranging from -110°F to 1050°F and pressures to 100,000 psi. SW464 has excellent anti-seize properties on steel bolts in super heated steam installations after exposure to 1050°F and 20% salt solutions..

Packaged twelve 16 fluid ounce (14 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW464	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase

Lubricants and Penetrants



SW715 Industrial White Grease Lubricant

SW715 is a highly-concentrated, all-purpose, heavy-duty spray for anything that squeaks, sticks or rusts. It leaves a long lasting film with excellent resistance to heat. SW715 will not wash away, run off or dry out. It is especially useful in the marine, automotive, glass & mirror, graphic arts, hardware and industrial maintenance trades.

Packaged twelve 16 fluid ounce (11 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW715	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW920 Industrial Polishing Oil

SW920 is for glass & mirror professionals and is formulated for grinding and polishing all metals and glass. SW920 minimizes belt loading and changing, increases production and improves finishes. It extends the working life of abrasive belts and wheels.

Packaged twelve 16 fluid ounce (12.75 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW920	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW945 Silicone Spray

SW945 retards corrosion. Makes cleaning easier and quicker. Dries fast with no greasy or oily film. It saves valuable time while it protects and preserves equipment. Colorless, non-staining, waxless and heatstable- unaffected by temperatures ranging from -40°C to 204°C. It has unusually low surface tension properties.

Packaged twelve 20 fluid ounce (11 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW945	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase



SW946 Silicone Spray & Release Agent

SW946 is colorless, non-staining, waxless and heat stable; unaffected by temperatures ranging from -40°C (-40°F) to over 200°C (392°F). This friction reducer results in speedier clean-up of parts and equipment and increased production through cleaner job processing. It remains dry and is non-staining.

Packaged twelve 20 fluid ounce (11 oz. net weight) cans per case.

CASES AND CANS	
PART NO. SW946	Call for Pricing
1-11 Cans	
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase

Lubricants and Penetrants



SW948 Electrical Grade Silicone Spray

SW948 is a multi-purpose lubricant that protects and waterproofs with a thin, clear, non-staining film. This non-hardening lubricant minimizes corrosion. Its low surface tension permits better coverage and deeper penetration.

Packaged twelve 20 fluid ounce_ (11 oz. net weight) cans per case.

CASES AND CANS

PART NO. SW948	
1-11 Cans	Call for Pricing
1-9 Cases (12-119 Cans)	
10-24 Cases (120-299 Cans)	
25+ (300+ Cans)	

5 Case Minimum Purchase