



SAFETY DATA SHEET

1. Identification

Product identifier: CAMIE 980 URETHANE RELEASE AGENT

Other means of identification

SDS number: RE1000002351

Recommended restrictions

Product use: Coating

Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name: Camie-Campbell, Inc.
Address: 1000 INTEGRAM DRIVE
PACIFIC, MO 63069
Telephone: 800-325-9572
Fax:

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

Flammable aerosol Category 1

Health Hazards

Skin Corrosion/Irritation Category 2
Toxic to reproduction Category 2
Specific Target Organ Toxicity -
Single Exposure Category 3¹
Specific Target Organ Toxicity -
Repeated Exposure Category 2
Aspiration Hazard Category 1

Target Organs

1. Narcotic effect.

Environmental Hazards

Acute hazards to the aquatic
environment Category 2
Chronic hazards to the aquatic
environment Category 2

Label Elements

Hazard Symbol:





Signal Word: Danger

Hazard Statement: Extremely flammable aerosol.
Causes skin irritation.
Suspected of damaging fertility or the unborn child.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
Toxic to aquatic life with long lasting effects.

Precautionary Statements

Prevention: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Use only outdoors or in a well-ventilated area. Do not breathe dust/fume/gas/mist/vapors/spray. Avoid release to the environment.

Response: IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. Call a POISON CENTER/doctor if you feel unwell. Specific treatment (see on this label). Take off contaminated clothing. Collect spillage.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place. Keep container tightly closed.

Disposal: Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.

Hazard(s) not otherwise classified (HNOC): None.

3. Composition/information on ingredients

Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Butane	106-97-8	20 - <50%
Hexane	110-54-3	25 - <50%
Naphtha (petroleum), hydrotreated light	64742-49-0	25 - <50%
Propane	74-98-6	10 - <20%
Naphtha (petroleum), heavy alkylate	64741-65-7	1 - <5%
Siloxanes and Silicones, di-Me	63148-62-9	1 - <5%
Cyclohexane	110-82-7	0.1 - <1%
Heptane	142-82-5	0.1 - <1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.



4. First-aid measures

Ingestion:	Rinse mouth. Call a physician or poison control center immediately. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.

Most important symptoms/effects, acute and delayed

Symptoms: No data available.

Hazards: No data available.

Indication of immediate medical attention and special treatment needed

Treatment: No data available.

5. Fire-fighting measures

General Fire Hazards: Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.

Suitable (and unsuitable) extinguishing media

Suitable extinguishing media: Use fire-extinguishing media appropriate for surrounding materials.

Unsuitable extinguishing media: Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical: Vapors may travel considerable distance to a source of ignition and flash back.

Special protective equipment and precautions for firefighters

Special fire fighting procedures: No data available.

Special protective equipment for fire-fighters: Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures: Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.



Methods and material for containment and cleaning up:

Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

Notification Procedures:

Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.

Environmental Precautions:

Do not contaminate water sources or sewer. Prevent further leakage or spillage if safe to do so. Avoid release to the environment.

7. Handling and storage

Precautions for safe handling:

Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.

Conditions for safe storage, including any incompatibilities:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Store locked up. Aerosol Level 3

8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	Type	Exposure Limit Values	Source
Butane	REL	800 ppm 1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	1,000 ppm	US. ACGIH Threshold Limit Values (03 2018)
	TWA	800 ppm 1,900 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Hexane	TWA	50 ppm 180 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	500 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	REL	50 ppm 180 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Naphtha (petroleum), hydrotreated light	TWA	50 ppm	US. ACGIH Threshold Limit Values (2008)
	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	REL	100 ppm 400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
Propane	TWA	100 ppm 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	1,000 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
Naphtha (petroleum), heavy alkylate	TWA	1,000 ppm 1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	PEL	100 ppm 400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	100 ppm 400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Cyclohexane	REL	100 ppm 400 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2010)
	TWA	100 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	300 ppm 1,050 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Heptane	REL	300 ppm 1,050 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	300 ppm 1,050 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	400 ppm 1,600 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	85 ppm 350 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29



			CFR 1910.1000) (02 2006)
	STEL	500 ppm 2,000 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	400 ppm	US. ACGIH Threshold Limit Values (02 2012)
	STEL	500 ppm	US. ACGIH Threshold Limit Values (02 2012)
	Ceil_Time	440 ppm 1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene, methyl-	STEL	150 ppm 560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	100 ppm 375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm 375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	300 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (2008)
	TWA	200 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	150 ppm 560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene	REL	0.1 ppm	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	1 ppm	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	25 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	0.5 ppm	US. ACGIH Threshold Limit Values (2008)
	STEL	2.5 ppm	US. ACGIH Threshold Limit Values (2008)
	STEL	5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	OSHA_ACT	0.5 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	TWA	10 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	50 ppm	US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	STEL	5 ppm	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	1 ppm	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (02 2006)
	STEL	1 ppm	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
Benzene, ethyl-	STEL	125 ppm 545 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	100 ppm 435 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	100 ppm 435 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	STEL	125 ppm 545 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	100 ppm 435 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	20 ppm	US. ACGIH Threshold Limit Values (12 2010)
Naphthalene	PEL	10 ppm 50 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm 50 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	10 ppm	US. ACGIH Threshold Limit Values (2008)
	STEL	15 ppm 75 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	10 ppm 50 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL	15 ppm 75 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Hexane (2,5-Hexanedion, without hydrolysis: Sampling time: End of shift.)	0.5 mg/l (Urine)	ACGIH BEL (03 2018)
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
Benzene (S-Phenylmercapturic acid: Sampling time: End of shift.)	25 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene (t,t-Muconic acid: Sampling time: End of shift.)	500 µg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, ethyl- (Sum of mandelic acid and phenylglyoxylic acid: Sampling time: End of shift.)	0.15 g/g (Creatinine in urine)	ACGIH BEL (02 2014)

Appropriate Engineering Controls

No data available.



Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).
Skin Protection	
Hand Protection:	No data available.
Other:	Wear suitable protective clothing. Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Observe good industrial hygiene practices. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104.44 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive limits	
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	2,068 - 3,447 hPa (20 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.



Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.

10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral

Product:	Not classified for acute toxicity based on available data.
Specified substance(s):	
Hexane	LD 50: > 2,000 mg/kg
Naphtha (petroleum), hydrotreated light	LD 50 (Rat): > 5,000 mg/kg
Naphtha (petroleum), heavy alkylate	LD 50: > 2,000 mg/kg



Cyclohexane LD 50 (Rat): > 5,000 mg/kg

Heptane LD 50 (Rat): > 5,000 mg/kg

Dermal

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Hexane LD 50 (Rabbit): > 2,000 mg/kg

Naphtha (petroleum),
hydrotreated light LD 50 (Rabbit): > 3,750 mg/kg

Naphtha (petroleum),
heavy alkylate LD 50: > 2,000 mg/kg

Cyclohexane LD 50 (Rabbit): > 2,000 mg/kg

Heptane LD 50 (Rabbit): > 2,000 mg/kg

Inhalation

Product: Not classified for acute toxicity based on available data.

Specified substance(s):

Butane LC 50: > 100 mg/l
LC 50: > 100 mg/l

Hexane LC 50 (Rat): > 31.86 mg/l
LC 50: > 5 mg/l

Naphtha (petroleum),
hydrotreated light LOAEL (Human): 2,400 mg/m³
LC 50 (Rat): > 7,630 mg/m³
LC 50: > 5 mg/l

Propane LC 50: > 100 mg/l
LC 50: > 100 mg/l

Naphtha (petroleum),
heavy alkylate LD 50: > 5 mg/l

Cyclohexane LC 50 (Rat): > 32,880 mg/m³

Heptane LC 50 (Rat): > 29.29 mg/l

Repeated dose toxicity

Product: No data available.

Specified substance(s):

Butane LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation
Experimental result, Key study

NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation
Experimental result, Key study

Hexane NOAEL (Mouse(Male), Inhalation, 13 Weeks): 500 ppm(m) Inhalation
Experimental result, Key study
LOAEL (Mouse(Male), Inhalation, 13 Weeks): 1,000 ppm(m) Inhalation
Experimental result, Key study

LOAEL (Rat(Male), Inhalation, 16 Weeks): 3,000 ppm(m) Inhalation
Experimental result, Key study

LOAEL (Mouse(Female), Inhalation, 13 Weeks): 500 ppm(m) Inhalation
Experimental result, Key study

Naphtha (petroleum),
hydrotreated light LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg Oral Read-
across based on grouping of substances (category approach), Key study



Propane	NOAEL (Rat(Female, Male), Dermal, 28 d): > 375 mg/kg Dermal Experimental result, Supporting study NOAEL (Rat(Female, Male), Inhalation): 10,000 mg/m ³ Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
Cyclohexane	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation, 13 - 18 Weeks): 7,000 ppm(m) Inhalation Experimental result, Key study NOAEL (Mouse(Female, Male), Inhalation, 13 - 18 Weeks): 500 ppm(m) Inhalation Experimental result, Key study
Heptane	NOAEL (Rat(Male), Inhalation): 12,470 mg/m ³ Inhalation Experimental result, Key study

Skin Corrosion/Irritation

Product:	No data available.
Specified substance(s):	
Cyclohexane	Review (Various): Irritating. in vivo (Rabbit): Not irritant Experimental result, Weight of Evidence study
Heptane	in vivo (Rabbit): Irritating Read-across based on grouping of substances (category approach), Key study

Serious Eye Damage/Eye Irritation

Product:	No data available.
Specified substance(s):	
Hexane	Rabbit, 1 - 72 hrs: Not irritating
Naphtha (petroleum), hydrotreated light	Rabbit, 24 - 72 hrs: Not irritating
Heptane	Rabbit, 24 - 72 hrs: Not irritating

Respiratory or Skin Sensitization

Product:	No data available.
Specified substance(s):	
Naphtha (petroleum), hydrotreated light	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Cyclohexane	Skin sensitization:, in vivo (Guinea pig): Non sensitising
Heptane	Skin sensitization:, in vivo (Guinea pig): Non sensitising

Carcinogenicity

Product:	No data available.
-----------------	--------------------

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens:

No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050):

No carcinogenic components identified

Germ Cell Mutagenicity

In vitro	
Product:	No data available.
In vivo	
Product:	No data available.



Reproductive toxicity

Product:	No data available.
Specified substance(s):	
Hexane	Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Single Exposure

Product:	No data available.
Specified substance(s):	
Hexane	Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Cyclohexane	Inhalation - vapor: Narcotic effect. - Category 3 with narcotic effects.
Heptane	Narcotic effect. - Category 3 with narcotic effects.

Specific Target Organ Toxicity - Repeated Exposure

Product:	No data available.
Specified substance(s):	
Hexane	Inhalation - vapor: Nervous System - Category 2

Target Organs

Specific Target Organ Toxicity - Single Exposure: Narcotic effect.

Aspiration Hazard

Product:	No data available.
Specified substance(s):	
Hexane	May be fatal if swallowed and enters airways.
Naphtha (petroleum), hydrotreated light	May be fatal if swallowed and enters airways.
Naphtha (petroleum), heavy alkylate	May be fatal if swallowed and enters airways.
Cyclohexane	May be fatal if swallowed and enters airways.
Heptane	May be fatal if swallowed and enters airways.

Other effects: No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish

Product:	No data available.
Specified substance(s):	
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Hexane	LC 50 (Fathead minnow (Pimephales promelas), 96 h): 2.101 - 2.981 mg/l Mortality
Naphtha (petroleum), hydrotreated light	LC 50 (96 h): 8.41 mg/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Siloxanes and Silicones, di-Me	LC 50 (Redear sunfish (Lepomis microlophus), 96 h): 26.27 - 56.73 mg/l Mortality
Cyclohexane	LC 50 (Pimephales promelas, 96 h): 4.53 mg/l Experimental result, Key study
Heptane	LC 50 (Mozambique tilapia (Tilapia mossambica), 96 h): 375 mg/l Mortality

Aquatic Invertebrates

Product:	No data available.
-----------------	--------------------



Specified substance(s):

Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Hexane	EC 50 (Daphnia magna, 48 h): 21.85 mg/l QSAR QSAR, Key study LC 50 (Water flea (Daphnia magna), 24 h): > 50 mg/l Mortality
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna, 48 h): 4.5 mg/l Experimental result, Key study
Siloxanes and Silicones, di-Me	LC 50 (Water flea (Daphnia magna), 48 h): 44.5 mg/l Mortality
Cyclohexane	EC 50 (Daphnia magna, 48 h): 0.9 mg/l Experimental result, Key study
Heptane	EC 50 (Daphnia magna, 48 h): 1.5 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:**Fish**

Product: No data available.

Specified substance(s):

Hexane	NOAEL (Oncorhynchus mykiss): 2.8 mg/l QSAR QSAR, Key study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna): 10 mg/l Other, Key study NOAEL (Daphnia magna): 2.6 mg/l Other, Key study
Heptane	NOAEL (Oncorhynchus mykiss): 1.284 mg/l QSAR QSAR, Key study

Aquatic Invertebrates

Product: No data available.

Specified substance(s):

Hexane	NOAEL (Daphnia magna): 4.888 mg/l QSAR QSAR, Key study
Naphtha (petroleum), hydrotreated light	EC 50 (Daphnia magna): 10 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2.6 mg/l Experimental result, Key study
Heptane	NOAEL (Daphnia magna): 0.17 mg/l Read-across based on grouping of substances (category approach), Key study EC 50 (Daphnia magna): 0.23 mg/l Read-across based on grouping of substances (category approach), Key study

Toxicity to Aquatic Plants

Product: No data available.

Persistence and Degradability**Biodegradation**

Product: No data available.

Specified substance(s):

Butane	100 % (385.5 h) Detected in water. Experimental result, Key study
Hexane	81 % Detected in water. Read-across based on grouping of substances (category approach), Key study
Naphtha (petroleum), hydrotreated light	90.35 % (28 d) Detected in water. Experimental result, Supporting study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Cyclohexane	77 % (28 d) Detected in water. Experimental result, Key study
Heptane	70 % Detected in water. Experimental result, Key study

BOD/COD Ratio

Product: No data available.



Bioaccumulative potential

Bioconcentration Factor (BCF)

Product:	No data available.
Specified substance(s):	
Hexane	Pimephales promelas, Bioconcentration Factor (BCF): 501.19 Aquatic sediment QSAR, Key study
Naphtha (petroleum), hydrotreated light	Bioconcentration Factor (BCF): 10 - 2,500 Aquatic sediment Estimated by calculation, Key study
Cyclohexane	Cyprinus carpio, Bioconcentration Factor (BCF): 37 - 129 Aquatic sediment Experimental result, Supporting study
Heptane	Bioconcentration Factor (BCF): 552 Aquatic sediment Estimated by calculation, Key study

Partition Coefficient n-octanol / water (log Kow)

Product:	No data available.
Specified substance(s):	
Naphtha (petroleum), hydrotreated light	Log Kow: > 2.4 - < 5.7 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 5.2 23 °C Yes Experimental result, Key study Log Kow: 2.2 - 6.1 23 °C Yes Experimental result, Key study

Mobility in soil: No data available.

Known or predicted distribution to environmental compartments

Butane	No data available.
Hexane	No data available.
Naphtha (petroleum), hydrotreated light	No data available.
Propane	No data available.
Naphtha (petroleum), heavy alkylate	No data available.
Siloxanes and Silicones, di-Me	No data available.
Cyclohexane	No data available.
Heptane	No data available.

Other adverse effects: Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Disposal instructions: Discharge, treatment, or disposal may be subject to national, state, or local laws.

Contaminated Packaging: No data available.

14. Transport information

DOT

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2.1
Label(s):	—
Packing Group:	II
Marine Pollutant:	No
Environmental Hazards:	No
Marine Pollutant	No
Special precautions for user:	Not regulated.



IMDG

UN Number:	UN 1950
UN Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es)	
Class:	2
Label(s):	—
EmS No.:	F-D, S-U
Packing Group:	—
Environmental Hazards:	Yes
Marine Pollutant	No
Special precautions for user:	Not regulated.

IATA

UN Number:	UN 1950
Proper Shipping Name:	Aerosols, flammable
Transport Hazard Class(es):	
Class:	2.1
Label(s):	—
Packing Group:	—
Environmental Hazards:	Yes
Marine Pollutant	No
Special precautions for user:	Not regulated.
Cargo aircraft only:	Allowed.

15. Regulatory information

US Federal Regulations

Restrictions on use: Not known.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

<u>Chemical Identity</u>	<u>OSHA hazard(s)</u>
Benzene	Flammability Cancer Aspiration Eye Blood Skin respiratory tract irritation Central nervous system

CERCLA Hazardous Substance List (40 CFR 302.4):

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Hexane	lbs. 5000
Cyclopentane, methyl-	lbs. 100
Propane	lbs. 100
Cyclohexane	lbs. 1000
Heptane	lbs. 100
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Benzene, ethyl-	lbs. 1000
Naphthalene	lbs. 100



Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard
Immediate (Acute) Health Hazards
Delayed (Chronic) Health Hazard
Flammable aerosol
Skin Corrosion/Irritation
Toxic to reproduction
Specific Target Organ Toxicity - Single Exposure
Specific Target Organ Toxicity - Repeated Exposure
Aspiration Hazard

SARA 302 Extremely Hazardous Substance

<u>Chemical Identity</u>	<u>Reportable quantity</u>	<u>Threshold Planning Quantity</u>
Hexane		

SARA 304 Emergency Release Notification

<u>Chemical Identity</u>	<u>Reportable quantity</u>
Butane	lbs. 100
Hexane	lbs. 5000
Cyclopentane, methyl-	lbs. 100
Propane	lbs. 100
Cyclohexane	lbs. 1000
Heptane	lbs. 100
Benzene, methyl-	lbs. 1000
Benzene	lbs. 10
Benzene, ethyl-	lbs. 1000
Naphthalene	lbs. 100

SARA 311/312 Hazardous Chemical

<u>Chemical Identity</u>	<u>Threshold Planning Quantity</u>
Butane	10000 lbs
Hexane	10000 lbs
Naphtha (petroleum), hydrotreated light	10000 lbs
Propane	10000 lbs
Naphtha (petroleum), heavy alkylate	10000 lbs
Siloxanes and Silicones, di-Me	10000 lbs
Cyclohexane	10000 lbs
Heptane	10000 lbs
Benzene, methyl-	10000 lbs
Benzene	10000 lbs
Benzene, ethyl-	10000 lbs
Naphthalene	10000 lbs

SARA 313 (TRI Reporting)

<u>Chemical Identity</u>	<u>Reporting threshold for other users</u>	<u>Reporting threshold for manufacturing and processing</u>
Hexane	lbs	lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):
Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3)
US State Regulations



US. California Proposition 65

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Hexane	Male reproductive toxin. 12 2017
Benzene, methyl-	Developmental toxin. 03 2008
Benzene	Developmental toxin. 03 2008
Benzene	Carcinogenic. 05 2011
Benzene	Male reproductive toxin. 03 2008
Benzene, ethyl-	Carcinogenic. 05 2011
Naphthalene	Carcinogenic. 05 2011

US. New Jersey Worker and Community Right-to-Know Act**Chemical Identity**

Butane
Hexane
Naphtha (petroleum), hydrotreated light
Cyclopentane, methyl-
Propane
Naphtha (petroleum), heavy alkylate

US. Massachusetts RTK - Substance List**Chemical Identity**

Benzene

US. Pennsylvania RTK - Hazardous Substances**Chemical Identity**

Butane
Hexane
Naphtha (petroleum), hydrotreated light
Cyclopentane, methyl-
Propane
Naphtha (petroleum), heavy alkylate

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations**Montreal protocol**

Hexane

Stockholm convention

Hexane

Rotterdam convention

Hexane

Kyoto protocol



Inventory Status:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	On or in compliance with the inventory
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	On or in compliance with the inventory
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	On or in compliance with the inventory
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16. Other information, including date of preparation or last revision
--

Issue Date:	11/14/2019
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.