SAFETY DATA SHEET




1. Identification

Product number	1000026440
Product identifier	SW048 4 OZ SPRAYWAY HS GLASS CLEANER LT 24PK
Company information	SPRAYWAY INC. 1000 Integram Dr Pacific, MO 63069 United States
Company phone	1-630-628-3000
Emergency telephone US	1-866-836-8855
Emergency telephone outside US	1-952-852-4646
Version #	01
Recommended use	CLEANER
Recommended restrictions	None known.
2. Hazard(s) identification	

Physical nazards
Health hazards
OSHA defined hazards

Label elements



Liquefied gas



	✓
Signal word	Warning
Hazard statement	Contains gas under pressure; may explode if heated.
Precautionary statement	
Prevention	Observe good industrial hygiene practices.
Response	If exposed or concerned: Get medical advice/attention.
Storage	Protect from sunlight. Store in a well-ventilated place.
Disposal	Dispose of waste and residues in accordance with local authority requirements.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
2-Butoxyethanol		111-76-2	2.5 - 10
Ethyl Alcohol		64-17-5	2.5 - 10
Butane		106-97-8	1 - 2.5
Propane		74-98-6	1 - 2.5
Other components below reportable levels			90 - 100

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	No adverse effects due to skin contact are expected.

Eye contact	No specific first aid measures noted.
Ingestion	Not likely, due to the form of the product.
Most important symptoms/effects, acute and delayed	Direct contact with eyes may cause temporary irritation.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
5. Fire-fighting measures	
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Cool containers exposed to flames with water until well after the fire is out.
General fire hazards	Contents under pressure. Pressurized container may explode when exposed to heat or flame.
6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat flame, sparks, or other sources of ignition. Ground and bond containers

while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Ground and bond containers when transferring material. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Purge air from system before introducing gas. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Do not re-use empty containers. Do not get in eyes, on skin, or on clothing. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. Level 1 Aerosol.
Conditions for safe storage, including any incompatibilities

Contents under pressure. Do not expose to heat or store at temperatures above 120°F/49°C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	PEL	240 mg/m3	
		50 ppm	
Ethyl Alcohol (CAS 64-17-5)	PEL	1900 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
US. ACGIH Threshold Limit Values			
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	20 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
Ethyl Alcohol (CAS 64-17-5)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to Chem	ical Hazards		
Components	Туре	Value	
2-Butoxyethanol (CAS 111-76-2)	TWA	24 mg/m3	
		5 ppm	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Ethyl Alcohol (CAS 64-17-5)	TWA	1900 mg/m3	
		1000 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
,		1000 ppm	

Biological limit values

ACGIH Biological Exposure Indices

Components	Value	Determinant	Specimen	Sampling Time	
2-Butoxyethanol (CAS 111-76-2)	200 mg/g	Butoxyacetic acid (BAA), with hydrolysis	Creatinine in urine	*	

* - For sampling details, please see the source document.

Exposure guidelines

Exposure guiaennes		
US - California OELs: Skin o	lesignation	
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
US - Minnesota Haz Subs: S	kin designation applies	
2-Butoxyethanol (CAS 11	1-76-2)	Skin designation applies.
US - Tennessee OELs: Skin	designation	
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
US NIOSH Pocket Guide to	Chemical Hazards: Skin desi	gnation
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
US. OSHA Table Z-1 Limits	for Air Contaminants (29 CFR	1910.1000)
2-Butoxyethanol (CAS 11	1-76-2)	Can be absorbed through the skin.
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.	
Individual protection measures,	such as personal protective	equipment
Eye/face protection	Wear safety glasses with side	e shields (or goggles).
Skin protection		
Hand protection	Wear appropriate chemical re supplier.	esistant gloves. Suitable gloves can be recommended by the glove
Other	Wear suitable protective clot	ning.

Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.	
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.	
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	

9. Physical and chemical properties

, ,		
Appearance		
Physical state	Gas.	
Form	Aerosol. Liquefied gas.	
Color	Not available.	
Odor	Not available.	
Odor threshold	Not available.	
рН	9.5 - 10.5 estimated	
Melting point/freezing point	Not available.	
Initial boiling point and boiling range	212 °F (100 °C) estimated	
Flash point	-156.0 °F (-104.4 °C) Propellant estimated	
Evaporation rate	Not available.	
Flammability (solid, gas)	Not available.	
Upper/lower flammability or exp	losive limits	
Flammability limit - lower (%)	Not available.	
Flammability limit - upper (%)	Not available.	
Explosive limit - lower (%)	Not available.	
Explosive limit - upper (%)	Not available.	
Vapor pressure	80 - 100 psig @70F estimated	
Vapor density	Not available.	
Relative density	Not available.	
Solubility(ies)		
Solubility (water)	Not available.	
Partition coefficient (n-octanol/water)	Not available.	
Auto-ignition temperature	Not available.	
Decomposition temperature	Not available.	
Viscosity	Not available.	
Other information		
Aerosol spray enclosed spa	ce	
Deflagration density > 2.52 g/cm3 Tested		
Aerosol spray ignition distance	< 15 cm Tested estimated	
Explosive properties	Not explosive.	
Oxidizing properties	Not oxidizing.	
Specific gravity	0.97 estimated	
10. Stability and reactivity		
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal conditions.	
Possibility of hazardous reactions	Hazardous polymerization does not occur.	

Heat. Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Conditions to avoid

Incompatible materials	Strong oxidizing agents.
Hazardous decomposition	No hazardous decomposition products are known.
products	

11. Toxicological information

Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.
Skin contact	2-Butoxy ethanol may be absorbed through the skin in toxic amounts if contact is repeated and prolonged. These effects have not been observed in humans.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.
Symptoms related to the physical, chemical and toxicological characteristics	Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

Acute toxicity

Components	Species	Test Results
2-Butoxyethanol (CAS 111-76-	-2)	
<u>Acute</u>		
Dermal		
LD50	Guinea pig	7.3 ml/kg, 4 Days
		0.23 ml/kg, 24 Hours
	Rabbit	435 mg/kg, 24 Hours
		0.68 ml/kg, 24 Hours
		0.63 ml/kg
	Rat	> 2000 mg/kg, 24 Hours
Inhalation		
LC50	Rabbit	400 ppm, 7 Hours
	Rat	450 ppm, 4 Hours
Oral		
LD100	Rabbit	695 mg/kg
LD50	Dog	> 695 mg/kg
	Guinea pig	1414 mg/kg
	Mouse	1519 mg/kg
	Rat	1746 mg/kg
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Ethyl Alcohol (CAS 64-17-5)		
<u>Acute</u>		
Inhalation		
LC50	Cat	85.41 mg/l, 4.5 Hours
		43.68 mg/l, 6 Hours
	Mouse	> 60000 ppm
		79.43 mg/l, 134 Minutes
	Rat	> 115.9 mg/l, 4 Hours
		51.3 mg/l, 6 Hours

Components	Species	Test Results	
Oral			
LD50	Monkey	6000 mg/kg	
	Mouse	10500 ml/kg	
	Pig	> 5000 mg/kg	
	Rat	10470 mg/kg	
		7800 ml/kg	
Propane (CAS 74-98-6)			
<u>Acute</u>			
Inhalation			
LC50	Mouse	1237 mg/l, 120 Minutes	
		52 %, 120 Minutes	
	Rat	1355 mg/l	
		658 mg/l/4h	
* -			
Skin corrosion/irritation	be based on additional component data not shown.		
	Not applicable. Direct contact with eyes may cause temporary irrita	tion	
Serious eye damage/eye irritation		lion.	
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.		
IARC Monographs. Overall	Evaluation of Carcinogenicity		
2-Butoxyethanol (CAS 11 OSHA Specifically Regulate	11-76-2) 3 Not classifiable as d Substances (29 CFR 1910.1001-1050)	to carcinogenicity to humans.	
Not regulated.	ogram (NTP) Report on Carcinogens		
Not listed.	· · · · · · · · · · · · · · · · · ·		
Reproductive toxicity	This product is not expected to cause reproductive	or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
Chronic effects	May be harmful if absorbed through skin.		
	2-Butoxy ethanol may be absorbed through the skir prolonged. These effects have not been observed		

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Componente		Creation	Test Results
Components		Species	Test Results
2-Butoxyethanol (CAS	111-76-2)		
Aquatic			
Fish	LC50	Inland silverside (Menidia beryllina)	1250 mg/l, 96 hours
Ethyl Alcohol (CAS 64	-17-5)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	7700 - 11200 mg/l, 48 hours

Components		Species	Test Results
Fish	LC50	Fathead minnow (Pimephales promelas) > 100.1 mg/l, 96 hours	

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-o	ctanol / water (log Kow)
2-Butoxyethanol	0.83
Butane	2.89
Ethyl Alcohol	-0.31
Propane	2.36
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport information

DOT

UN number	UN1950
UN proper shipping name	Aerosols, non-flammable, (each not exceeding 1 L capacity)
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Special precautions for user	Not available.
Packaging exceptions	306
Packaging non bulk	None
Packaging bulk	None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

UN number UN proper shipping name Transport hazard class(es)	UN1950 Aerosols, non-flammable
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	No.
ERG Code	2L
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Other information	
Passenger and cargo aircraft	Allowed with restrictions.

Cargo aircraft only	Allowed with restrictions.
Packaging Exceptions	LTD QTY
IMDG	
UN number	UN1950
UN proper shipping name	AEROSOLS
Transport hazard class(es)	
Class	2.2
Subsidiary risk	-
Label(s)	2.2
Packing group	Not applicable.
Environmental hazards	
Marine pollutant	No.
EmS	Not available.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
Packaging Exceptions	LTD QTY
Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
DOT	

NON-FLAMMABLE GAS 2



General information

Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Re	authorization Act of 1986 (S	SARA)		
Hazard categories	Immediate Hazard - No	,		
	Delayed Hazard - No			
	Fire Hazard - No Pressure Hazard - Yes			
	Reactivity Hazard - No			
SARA 302 Extremely hazard	lous substance			
Not listed.				
SARA 311/312 Hazardous chemical	No			
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
2-Butoxyethanol		111-76-2	2.5 - 10	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Pollutar	nts (HAPs) List		
Not regulated.		X Y		
Clean Air Act (CAA) Section	112(r) Accidental Release I	Prevention (40 CFR	68.130)	
Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. California Controlled Su	ubstances. CA Department of	of Justice (California	Health and Safety Co	de Section 11100)
Not listed.	•	·	-	
US. California. Candidate Cl (a))	nemicals List. Safer Consur	ner Products Regula	ations (Cal. Code Regs	s, tit. 22, 69502.3, subd.
2-Butoxyethanol (CAS 11	1-76-2)			
Butane (CAS 106-97-8)	whether a list			
US. Massachusetts RTK - Si				
2-Butoxyethanol (CAS 11 Butane (CAS 106-97-8)	1-70-2)			
Ethyl Alcohol (CAS 64-17	·-5)			
Propane (CAS 74-98-6)				
US. New Jersey Worker and		Act		
2-Butoxyethanol (CAS 11 Butane (CAS 106-97-8)	1-76-2)			
Ethyl Alcohol (CAS 64-17	' -5)			
Propane (CAS 74-98-6)	- /			
US. Pennsylvania Worker ar		w Law		
2-Butoxyethanol (CAS 11	1-76-2)			
Butane (CAS 106-97-8) Ethyl Alcohol (CAS 64-17	(-5)			
Propane (CAS 74-98-6)	-0)			
US. Rhode Island RTK				
Butane (CAS 106-97-8) Propane (CAS 74-98-6)				
US. California Proposition 6	5			
	Nater and Toxic Enforcement isted as carcinogens or reproc		tion 65): This material is	not known to contain
International Inventories				
Country(s) or region	Inventory name			On inventory (yes/no)*
Australia	Australian Inventory of Che	mical Substances (Al	CS)	Yes
Canada	Domestic Substances List (DSL)		Yes
Canada	Non-Domestic Substances	List (NDSL)		No
China	Inventory of Existing Chemi	cal Substances in Ch	ina (IECSC)	Yes
Europe	European Inventory of Exist	ting Commercial Che	mical	Yes
	Substances (EINECS)			

Country(s) or region	Inventory name	On inventory (yes/no)*
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	02-22-2018
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names