

SAFETY DATA SHEET

1. Identification

| 1. Identification | |
|-----------------------------------|-----------------------------------------------------------------------|
| Product number | 1000011816 |
| Product identifier | SW 575 CLEAN BREEZE AIR FRESHENER |
| Company information | Sprayway, Inc. 1000 INTEGRAM DR Pacific, MO 63069 United States |
| Company phone | 1-630-628-3000 |
| Emergency telephone US | 1-866-836-8855 |
| Emergency telephone outside US | 1-952-852-4646 |
| Version # | 01 |
| Recommended use | Air Freshener |
| Recommended restrictions | None known. |
| 2. Hazard(s) identification | |

Physical hazards Health hazards OSHA defined hazards

Label elements

Flammable aerosols Aspiration hazard Not classified.

Category 1 Category 1



| Signal word | Danger |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Hazard statement | Extremely flammable aerosol. May be fatal if swallowed and enters airways. |
| Precautionary statement | |
| Prevention | Keep away from heat/sparks/open flames/hot surfaces No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. |
| Response | If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting. |
| Storage | Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. |
| Disposal | Dispose of contents/container in accordance with local/regional/national/international regulations. |
| Hazard(s) not otherwise classified (HNOC) | Combustible. |
| Supplemental information | None. |
| | |

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|------------------------------------------------|--------------------------|------------|----------|
| Distillates (Petroleum), Hydrotreated Light | | 64742-47-8 | 10 - 20 |
| Butane | | 106-97-8 | 2.5 - 10 |
| Propane | | 74-98-6 | 2.5 - 10 |
| Other components below report | table levels | | 60 - 80 |

Other components below reportable levels

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Skin contact If symptoms develop move victim to fresh air. Get medical attention if symptoms persist. Wash off with soap and water. Get medical attention if irritation develops and persists.

| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
|------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Aspiration may cause pulmonary edema and pneumonitis. |
| Indication of immediate medical attention and special treatment needed | Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |
| 5. Fire-fighting measures | |
| Suitable extinguishing media | Alcohol resistant foam. Powder. Dry chemicals. Carbon dioxide (CO2). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. |
| Fire fighting equipment/instructions | Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes. |
| General fire hazards | Extremely flammable aerosol. Combustible. |
| 6. Accidental release meas | sures |
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Use water spray to reduce vapors or divert vapor cloud drift. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |
| 7. Handling and storage | |
| Precautions for safe handling | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Level 1 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Туре | Value | |
|-----------------------|------|------------|--|
| Propane (CAS 74-98-6) | PEL | 1800 mg/m3 | |

| US. | OSHA Ta | ble Z-1 Limits | for Air Co | ontaminants | (29 CFR | 1910.1000) |
|-----|----------------|----------------|------------|-------------|---------|------------|
| | | | | | (| |

| Components | Type | Value | |
|---------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--|
| - | | 1000 ppm | |
| US. ACGIH Threshold Lim Components | it Values Type | Value | |
| Butane (CAS 106-97-8) | STEL | 1000 ppm | |
| US. NIOSH: Pocket Guide Components | to Chemical Hazards Type | Value | |
| Butane (CAS 106-97-8) | TWA | 1900 mg/m3 800 ppm | |
| Propane (CAS 74-98-6) | TWA | 1800 mg/m3 1000 ppm | |
| logical limit values | No biological exposure limits noted t | for the ingredient(s). | |
| propriate engineering htrols | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. | | |
| ividual protection measure | s, such as personal protective equipr | nent | |
| Eye/face protection | Face shield is recommended. Wear safety glasses with side shields (or goggles). | | |
| Skin protection | | | |
| Hand protection | Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier. | | |
| Other | Wear suitable protective clothing. | Wear suitable protective clothing. | |
| Respiratory protection | If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator. | | |
| Thermal hazards | Wear appropriate thermal protective | clothing, when necessary. | |
| neral hygiene nsiderations | When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. | | |
| | | | |

9. Physical and chemical properties

| Appearance | |
|----------------------------------------------|--------------------------------------------|
| Physical state | Gas. |
| Form | Aerosol. |
| Color | Not available. |
| Odor | Not available. |
| Odor threshold | Not available. |
| рН | Not available. |
| Melting point/freezing point | Not available. |
| Initial boiling point and boiling range | 212 °F (100 °C) estimated |
| Flash point | -156.0 °F (-104.4 °C) Propellant estimated |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 1.9 % estimated |
| Flammability limit - upper (%) | 9.5 % estimated |
| Explosive limit - lower (%) | Not available. |

Explosive limit - upper (%) Not available.

| Vanar processo | 24.04 pair @70E astimated |
|--------------------------------------------|-----------------------------------------------------------------------------------------------|
| Vapor pressure | 24.94 psig @70F estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 469.4 °F (243 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |
| Specific gravity | 0.784 estimated |
| 10. Stability and reactivity | |
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |

| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
|---------------------------------------|-----------------------------------------------------------------------------------------------|
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | Hazardous polymerization does not occur. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Strong oxidizing agents. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| Inhalation | No adverse effects due to inhalation are expected. | |
|------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------------------------------|--|
| Skin contact | No adverse effects due to skin contact are expected. | |
| Eye contact | Direct contact with eyes may cause temporary irritation. | |
| Ingestion | Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. | |
| Symptoms related to the physical, chemical and toxicological characteristics | Aspiration may cause pulmonary edema and pneumonitis. | |

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

| Components | Species | Test Results |
|-----------------------------|-----------------------------------|------------------------|
| Butane (CAS 106-97-8) | | |
| Acute | | |
| Inhalation | | |
| LC50 | Mouse | 1237 mg/l, 120 Minutes |
| | | 52 %, 120 Minutes |
| | Rat | 1355 mg/l |
| Distillates (Petroleum), Hy | drotreated Light (CAS 64742-47-8) | |
| Acute | | |
| Dermal | | |
| LD50 | Rabbit | > 2000 mg/kg |
| | | > 2000 mg/kg, 24 Hours |
| Inhalation | | |
| LC50 | Rat | > 7.5 mg/l, 6 Hours |
| | | > 4.6 mg/l, 4 Hours |
| | | |

| Components | ts Species | | Test Results | |
|--------------------------------------------------------------------------------------------------------|----------------------------------------------------------|------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|--|
| Oral LD50 | | | > 5000 mg/kg | |
| Propane (CAS 74-98-6) | | | | |
| <u>Acute</u> | | | | |
| Inhalation | | | | |
| LC50 | Mouse | | 1237 mg/l, 120 Minutes | |
| | | | 52 %, 120 Minutes | |
| | Rat | | 1355 mg/l | |
| | | | 658 mg/l/4h | |
| * Estimates for product may | be based on ac | dditional component data not shown. | | |
| Skin corrosion/irritation | - | skin contact may cause temporary irrita | | |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. | | | |
| Respiratory or skin sensitization | on | | | |
| Respiratory sensitization | - | atory sensitizer. | | |
| Skin sensitization | • | t is not expected to cause skin sensitiz | | |
| Germ cell mutagenicity | mutagenic o | or genotoxic. | onents present at greater than 0.1% are | |
| Carcinogenicity | This produc | t is not considered to be a carcinogen | by IARC, ACGIH, NTP, or OSHA. | |
| Not listed. OSHA Specifically Regular Not regulated. US. National Toxicology P Not listed. | | s (29 CFR 1910.1001-1050) Report on Carcinogens | | |
| Reproductive toxicity | This produc | This product is not expected to cause reproductive or developmental effects. | | |
| Specific target organ toxicity - single exposure | | | | |
| Specific target organ toxicity - repeated exposure | Not classifie | ed. | | |
| Aspiration hazard | May be fatal if swallowed and enters airways. | | | |
| 12. Ecological information | on | | | |
| Ecotoxicity | | | azardous. However, this does not exclude the narmful or damaging effect on the environment. | |
| Components | | Species | Test Results | |
| Distillates (Petroleum), Hydr Aquatic | otreated Light (| CAS 64742-47-8) | | |
| Fish | LC50 | Rainbow trout,donaldson trout (Oncorhynchus mykiss) | 2.9 mg/l, 96 hours | |
| * Estimates for product may | be based on a | dditional component data not shown. | | |
| Persistence and degradability | | available on the degradability of this pro- | oduct. | |
| Bioaccumulative potential | | 3 , | | |
| Partition coefficient n-octa | anol / water (lo | g Kow) | | |
| Butane | | 2.89 | | |
| | | 2.36 | | |
| Propane | N1 1 1 | 1.1.1 | | |
| | No data ava | | e depletion, photochemical ozone creation | |

13. Disposal considerations

| Disposal instructions | Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. | |
|------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Local disposal regulations | Dispose in accordance with all applicable regulations. | |
| Hazardous waste code | The waste code should be assigned in discussion between the user, the producer and the waste disposal company. | |
| Waste from residues / unused products | Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions). | |
| Contaminated packaging | Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. | |

14. Transport information

DOT

| UN number UN proper shipping name Transport hazard class(es) | UN1950 Aerosols, flammable, (each not exceeding 1 L capacity) |
|--------------------------------------------------------------------|-------------------------------------------------------------------------|
| Class | 2.1 |
| Subsidiary risk | - |
| Label(s) | 2.1 |
| Packing group | Not applicable. |
| Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. |
| Special provisions | N82 |
| Packaging exceptions | 306 |
| Packaging non bulk | None |
| Packaging bulk | None |

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking.

ΙΑΤΑ

| 171 | ~ | | |
|-----|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------|--|
| | UN number | UN1950 | |
| | UN proper shipping name | Aerosols, flammable | |
| | Transport hazard class(es) | | |
| | Class | 2.1 | |
| | Subsidiary risk | - | |
| | Label(s) | 2.1 | |
| | Packing group | Not applicable. | |
| | Environmental hazards | No. | |
| | ERG Code | 10L | |
| | Special precautions for user | Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. | |
| | Other information | | |
| | Passenger and cargo aircraft | Allowed with restrictions. | |
| | Cargo aircraft only | Allowed with restrictions. | |
| | Packaging Exceptions | LTD QTY | |
| IME |)G | | |
| | UN number | UN1950 | |
| | UN proper shipping name | AEROSOLS | |
| | Transport hazard class(es) | | |
| | Class | 2.1 | |
| | Subsidiary risk | - | |
| | Label(s) | None | |
| | Packing group | Not applicable. | |
| | Environmental hazards | | |
| | Marine pollutant | No. | |
| | EmS | F-D, S-U | |
| | | | |

Packaging Exceptions Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

DOT

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety instructions, SDS and emergency procedures before handling. LTD QTY Not applicable.



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance Not listed. SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6) Safe Drinking Water Act Not regulated. (SDWA)

US state regulations

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.
- (a))

Butane (CAS 106-97-8)

US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

| Country(s) or region | Inventory name | On inventory (yes/no)* |
|-----------------------------|---------------------------------------------------------------------------|------------------------|
| Australia | Australian Inventory of Chemical Substances (AICS) | No |
| Canada | Domestic Substances List (DSL) | Yes |
| Canada | Non-Domestic Substances List (NDSL) | No |
| China | Inventory of Existing Chemical Substances in China (IECSC) | No |
| Europe | European Inventory of Existing Commercial Chemical Substances (EINECS) | No |
| Europe | European List of Notified Chemical Substances (ELINCS) | No |
| Japan | Inventory of Existing and New Chemical Substances (ENCS) | No |
| Korea | Existing Chemicals List (ECL) | No |
| New Zealand | New Zealand Inventory | No |
| Philippines | Philippine Inventory of Chemicals and Chemical Substances (PICCS) | No |
| United States & Puerto Rico | Toxic Substances Control Act (TSCA) Inventory | Yes |

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

| Issue date | 10-10-2017 | |
|----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Version # | 01 | |
| Disclaimer | The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. | |
| Revision information | Product and Company Identification: Alternate Trade Names Other information, including date of preparation or last revision: Disclaimer | |