

# SAFETY DATA SHEET

### 1. Identification

**OSHA** defined hazards

Label elements

1. Identification		
Product number	100009282	
Product identifier	SW725 WELDER'S ANTI-SPATTER SPRAY	
Company information	Sprayway, Inc. 1000 INTEGRAM DR Pacific, MO 63069 United States	
Company phone	1-630-628-3000	
Emergency telephone US	1-866-836-8855	
Emergency telephone outside US	1-952-852-4646	
Version #	01	
Recommended use	Not available.	
Recommended restrictions	None known.	
2. Hazard(s) identification		
Physical hazards	Flammable aerosols Category	
Health hazards	Not classified.	

Not classified.

Signal word Danger Extremely flammable aerosol. Hazard statement **Precautionary statement** Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open Prevention flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands after handling. Response Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Storage Disposal Dispose of waste and residues in accordance with local authority requirements. Hazard(s) not otherwise Combustible. classified (HNOC) Supplemental information None.

#### 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
Propane		74-98-6	20 - 40
Other components below reportable levels			40 - 60

Other components below reportable levels

\*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation	If symptoms develop move victim to fresh air. Get medical attention if symptoms persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.

Most important symptoms/effects, acute and delayed	Dizziness.		
Indication of immediate medical attention and special treatment needed	Treat symptomatically.		
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Foam. Powder. Dry chemicals. Carbon dioxide (CO2).		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.		
Special protective equipment and precautions for firefighters	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.		
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Cool containers exposed to heat with water spray and remove container, if no risk is involved. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.		
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. In the event of fire and/or explosion do not breathe fumes.		
General fire hazards	Extremely flammable aerosol. Combustible.		
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.		
Methods and materials for containment and cleaning up	Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. For waste disposal, see section 13 of the SDS.		
Environmental precautions	Avoid discharge into drains, water courses or onto the ground.		
7. Handling and storage			
Precautions for safe handling	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged or repeated contact with skin. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.		
Conditions for safe storage,	Level 3 Aerosol.		
including any incompatibilities	Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of		

### 8. Exposure controls/personal protection

#### **Occupational exposure limits**

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)			
Components	Туре	Value	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	

spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Level 2 Aerosol.

US. ACGIH Threshold Limit Components	Values Type	Value	
Butane (CAS 106-97-8)	STEL	1000 ppm	
US. NIOSH: Pocket Guide to	Chemical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	
		800 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	
Biological limit values	No biological exposure limits noted	for the ingredient(s).	
Appropriate engineering controls	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.		
Individual protection measures,	such as personal protective equip	ment	
Eye/face protection	Wear safety glasses with side shields (or goggles).		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.		
Other	Wear suitable protective clothing.		
Respiratory protection	If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an air-supplied respirator.		
Thermal hazards	Wear appropriate thermal protective	e clothing, when necessary.	
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

## 9. Physical and chemical properties

	•
Appearance	
Physical state	Gas.
Form	Aerosol.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.
рН	Not available.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	662 °F (350 °C) estimated
Flash point	-156.0 °F (-104.4 °C) Propellant estimated
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower 1.9 % estimated (%)	
Flammability limit - upper (%)	9.5 % estimated
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	70 - 80 psig @70F estimated
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.

Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion (NFPA 30B)	35.53 kJ/g estimated
Oxidizing properties	Not oxidizing.
Specific gravity	0.862 - 0.872 estimated

## 10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.	
Chemical stability	Material is stable under normal conditions.	
Possibility of hazardous reactions	Hazardous polymerization does not occur.	
Conditions to avoid	Avoid temperatures exceeding the flash point. Contact with incompatible materials.	
Incompatible materials	Strong oxidizing agents. Nitrates. Fluorine. Chlorine.	
Hazardous decomposition products	No hazardous decomposition products are known.	

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	No adverse effects due to inhalation are expected.		
Skin contact	No adverse effects due to skin contact are expected.		
Eye contact	Direct contact with eyes may cause temporary irritation.		
Ingestion	Expected to be a low ingestion hazard.		
Symptoms related to the physical, chemical and toxicological characteristics	Dizziness.		

#### Information on toxicological effects

#### Acute toxicity

SW725 WELDER'S ANTI-SPAT Acute Inhalation	TTER SPRAY	
Inhalation		
LC50	Rat	1316 mg/l/4h
Components	Species	Test Results
Butane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
Propane (CAS 74-98-6)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l

Components	Species	Test Results	
		658 mg/l/4h	
	e based on additional component of		
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.		
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.		
Respiratory or skin sensitization	1		
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensitization.		
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	This product is not considered to	be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
Not listed.	Evaluation of Carcinogenicity d Substances (29 CFR 1910.100 <sup>-</sup>	-1050)	
	ogram (NTP) Report on Carcinog	ens	
Reproductive toxicity	This product is not expected to c	ause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	Not classified.		
Aspiration hazard	Not likely, due to the form of the product.		
12. Ecological information	1		
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environmen		
Product	Species	Test Results	
SW725 WELDER'S ANTI-SP	ATTER SPRAY		
Aquatic			
Fish	LC50 Fish	2773 mg/L, 96 Hours	
* Estimates for product may b	e based on additional component of	data not shown.	
Persistence and degradability	No data is available on the degra	idability of this product.	
Bioaccumulative potential			
Partition coefficient n-octan Butane	2.89		
Propane Mobility in soil	No data available.	.36	
Other adverse effects	No other adverse environmental	effects (e.g. ozone depletion, photochemical ozone creation lobal warming potential) are expected from this component.	
13. Disposal consideration			
Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.		
Local disposal regulations	Dispose in accordance with all a		
Hazardous waste code	The waste code should be assigned by a state of the state	ned in discussion between the user, the producer and the waste	
Waste from residues / unused products		cal regulations. Empty containers or liners may retain some nd its container must be disposed of in a safe manner (see:	
Contaminated packaging	Since emptied containers may re	tain product residue, follow label warnings even after container is d be taken to an approved waste handling site for recycling or ontainers.	
Product name: SW725 WELDER'S A		SDS US	

## 14. Transport information

DO	т	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Special precautions for user	Not available.
	Special provisions	N82
	Packaging exceptions	306
	Packaging non bulk	None
	Packaging bulk	None
IAT	A	
	UN number	UN1950
	UN proper shipping name	Aerosols, flammable
	Transport hazard class(es)	
	Class	2.1
	Subsidiary risk	-
	Label(s)	2.1
	Packing group	Not applicable.
	Environmental hazards	No.
	ERG Code	10L
		Read safety instructions, SDS and emergency procedures before handling.
	Other information	
	Passenger and cargo	Allowed with restrictions.
	aircraft	Allowed with restrictions
	Cargo aircraft only	Allowed with restrictions. LTD QTY
імі	Packaging Exceptions	LIDQIT
		1111050
	UN number	UN1950 AEROSOLS
	UN proper shipping name Transport hazard class(es)	AEROSOLS
	Class	2.1
		2.1
	Subsidiary risk Label(s)	- None
	Packing group	Not applicable.
	Environmental hazards	Not applicable.
		No.
	Marine pollutant EmS	F-D, S-U
		Read safety instructions, SDS and emergency procedures before handling.
	Packaging Exceptions	LTD QTY
Tra	insport in bulk according to	Not applicable.
	nex II of MARPOL 73/78 and	
	BC Code	
DO		
50		





#### 15. Regulatory information

#### **US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

**Hazard categories** 

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

Immediate Hazard - No Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No chemical

SARA 313 (TRI reporting) Not regulated.

#### Other federal regulations

#### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act Not regulated. (SDWA)

#### **US state regulations**

- US. California Controlled Substances. CA Department of Justice (California Health and Safety Code Section 11100) Not listed.
- US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Butane (CAS 106-97-8)

#### US. Massachusetts RTK - Substance List

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. New Jersey Worker and Community Right-to-Know Act

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

US. Pennsylvania Worker and Community Right-to-Know Law

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. Rhode Island RTK

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

#### US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

### 16. Other information, including date of preparation or last revision

Issue date	11-12-2018
Version #	01
Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
Revision information	Product and Company Identification: Alternate Trade Names Hazard(s) identification: Response Composition / Information on Ingredients: Component Summary Handling and storage: Conditions for safe storage, including any incompatibilities Physical & Chemical Properties: Multiple Properties