

Version: 1.0 Revision Date: 04/15/2019

SAFETY DATA SHEET

1. Identification

Product identifier: GEL VANDAL MARK REMOVER

Other means of identification SDS number: RE1000010423

Recommended restrictions

Product Use: Cleaner Restrictions on use: Not known.

Manufacturer/Importer/Distributor Information

Manufacturer

Company Name:	Sprayway, Inc.
Address:	1000 INTEGRAM DR
	Pacific,MO 63069
Telephone:	630-628-3000
Fax:	

Emergency telephone number: 1-866-836-8855

2. Hazard(s) identification

Hazard Classification

Physical Hazards

,	
Flammable aerosol	Category 1
Health Hazards	
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2A
Toxic to reproduction	Category 2
Aspiration Hazard	Category 1

Environmental Hazards

Acute hazards to the aquatic	Category 3
environment	

Label Elements

Hazard Symbol:





Signal Word:	Danger
Hazard Statement:	Extremely flammable aerosol. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May be fatal if swallowed and enters airways. Harmful to aquatic life.
Precautionary Statements	
Prevention:	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Avoid release to the environment.
Response:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF ON SKIN: Wash with plenty of water/ If skin irritation occurs: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor/ Do NOT induce vomiting. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50 oC/122oF. Store locked up.
Disposal:	Dispose of contents/container to an appropriate treatment and disposal facility in accordance with applicable laws and regulations, and product characteristics at time of disposal.
Hazard(s) not otherwise classified (HNOC):	None.

3. Composition/information on ingredients



Mixtures

Chemical Identity	CAS number	Content in percent (%)*
Benzene, methyl-	108-88-3	10 - <25%
2-Propanone	67-64-1	5 - <10%
Propane	74-98-6	5 - <10%
Butane	106-97-8	5 - <10%
Ethanol, 2-butoxy-	111-76-2	1 - <5%
Ethanol, 2-(2-butoxyethoxy)-	112-34-5	1 - <5%
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with bentonite	71011-25-1	1 - <5%
Sodium hydroxide (Na(OH))	1310-73-2	0.1 - <1%
Morpholine	110-91-8	0.1 - <1%
Quartz (SiO2)	14808-60-7	0 - <0.1%
Ethanol, 2-methoxy-	109-86-4	0 - <0.1%
1,2-Ethanediamine	107-15-3	0 - <0.1%
Morpholine, 4-ethyl-	100-74-3	0 - <0.1%

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

4. First-aid measures

Ingestion:	Call a physician or poison control center immediately. Rinse mouth. Never give liquid to an unconscious person. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.
Inhalation:	Move to fresh air.
Skin Contact:	Immediately flush with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash contaminated clothing before reuse. Get medical attention.
Eye contact:	Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention.
Most important symptoms/effe	ects, acute and delayed
Symptoms:	No data available.
Hazards:	No data available.
Indication of immediate medic	al attention and special treatment needed
Treatment:	No data available.
5. Fire-fighting measures	
General Fire Hazards:	Use water spray to keep fire-exposed containers cool. Fight fire from a protected location. Move containers from fire area if you can do so without risk.
SDS_US - RE1000010423	3/23



Suitable (and unsuitable) extinguishing media

Suitable extinguishing media:	Use fire-extinguishing media appropriate for surrounding materials.
Unsuitable extinguishing media:	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical:	Vapors may travel considerable distance to a source of ignition and flash back.
Special protective equipment an	d precautions for firefighters
Special fire fighting procedures:	No data available.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
6. Accidental release measure	S
Personal precautions, protective equipment and emergency procedures:	Ventilate closed spaces before entering them. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Keep upwind. See Section 8 of the SDS for Personal Protective Equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Keep unauthorized personnel away.
Methods and material for containment and cleaning up:	Absorb spill with vermiculite or other inert material, then place in a container for chemical waste. Dike far ahead of larger spill for later recovery and disposal.
Notification Procedures:	Dike for later disposal. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop leak if you can do so without risk.
Environmental Precautions:	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water sources or sewer.
7. Handling and storage	
Precautions for safe handling:	Avoid contact with eyes. Wash hands thoroughly after handling. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Use personal protective equipment as required. Avoid contact with skin.
Conditions for safe storage, including any incompatibilities:	Store locked up. Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use. Aerosol Level 2



8. Exposure controls/personal protection

Control Parameters

Occupational Exposure Limits

Chemical Identity	emical Identity Type Exposure Limit Values		Source	
Benzene, methyl-	STEL	150 ppm	560 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	10 ppm	37 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (02 2012)
	REL	100 ppm	375 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	100 ppm	375 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	150 ppm	560 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	Ceiling	300 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	Ceiling	500 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	AN ESL		1,200 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	200 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	MAX. CONC	500 ppm		US. OSHA Table Z-2 (29 CFR 1910.1000) (02 2006)
	ST ESL		4,500 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	STEL	150 ppm	580 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		1,200 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	100 ppm	375 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL	150 ppm	560 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	AN ESL		320 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
2-Propanone	STEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL		1,780 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	PEL	1,000 ppm	2,400 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		2,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	250 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA	750 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceiling	3,000 ppm		US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	STEL	500 ppm		US. ACGIH Threshold Limit Values (03 2015)
	TWA PEL	500 ppm	1,200 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		7,800 µg/m3	US. Texas. Effects Screening Levels (Texas



				Commission on Environmental Quality) (11 2016)
	AN ESL		4,800 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	750 ppm	1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	ST ESL		3,300 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	250 ppm	590 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	STEL		2,400 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Propane	REL	1,000 ppm	1,800 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	1,000 ppm	1,800 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA		1,800 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	1,000 ppm	1,800 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
Butane	REL	800 ppm	1,900 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA		1,900 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	STEL TWA	1,000 ppm 800 ppm	1,900 mg/m3	US. ACGIH Threshold Limit Values (03 2018) US. OSHA Table Z-1-A (29 CFR 1910.1000)
	AN ESL		3,000 ppb	(1989) US. Texas. Effects Screening Levels (Texas
			-,	Commission on Environmental Quality) (11 2016)
	AN ESL		7,100 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA PEL	800 ppm	1,900 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		66,000 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		28,000 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Ethanol, 2-butoxy-	TWA	20 ppm	100 / 0	US. ACGIH Threshold Limit Values (2008)
	TWA	25 ppm	120 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	REL	5 ppm	24 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	50 ppm	240 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA PEL	20 ppm	97 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	TWA	25 ppm	120 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	AN ESL		760 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		3,700 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		2,900 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		600 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11



				2016)
Ethanol, 2-(2-butoxyethoxy)- - Inhalable fraction and vapor.	TWA	10 ppm		US. ACGIH Threshold Limit Values (03 2013)
Ethanol, 2-(2-butoxyethoxy)-	ST ESL		670 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		67 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Sodium hydroxide (Na(OH))	Ceiling		2 mg/m3	US. ACGIH Threshold Limit Values (2008)
	Ceiling		2 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	Ceil_Time		2 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL		2 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	Ceiling		2 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	Ceiling		2 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
Sodium hydroxide (Na(OH)) - Particulate.	AN ESL		2 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		20 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Morpholine	TWA	20 ppm		US. ACGIH Threshold Limit Values (2008)
	STEL	30 ppm	105 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	REL	20 ppm	70 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	PEL	20 ppm	70 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	20 ppm	70 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	STEL	30 ppm	105 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA STEL	20 ppm	70 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA PEL	30 ppm	105 mg/m3 70 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008) US. California Code of Regulations, Title 8,
		20 ppm	-	Section 5155. Airborne Contaminants (09 2006)
	STEL	30 ppm	105 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		36 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		11 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		40 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
Quartz (SiO2) - Respirable fraction.	TWA		0.025 mg/m3	US. ÁCGIH Threshold Limit Values (2008)
Quartz (SiO2) - Respirable	REL		0.05 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)

SDS_US - RE1000010423



Quartz (SiO2) - Respirable dust.	TWA		0.05 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
	OSHA_AC T		0.025 mg/m3	US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) (03 2016)
Quartz (SiO2) - Respirable dust.	PEL		0.05 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (03 2016)
	TWA		0.1 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA		0.1 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Quartz (SiO2) - Respirable.	TWA		2.4 millions of particles per cubic foot	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
			of air	
	TWA		0.1 mg/m3	US. OSHA Table Z-3 (29 CFR 1910.1000) (2000)
Quartz (SiO2) - Respirable dust.	TWA PEL		0.05 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (10 2016)
Quartz (SiO2) - Particulate.	ST ESL		14 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		0.27 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11
Ethanol, 2-methoxy-	TWA	0.1 ppm		2016) US. ACGIH Threshold Limit Values (2008)
	REL	0.1 ppm	0.3 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	25 ppm	80 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA	25 ppm	80 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA PEL	5 ppm	16 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	ST ESL		50 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		16 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	PEL	25 ppm	80 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		5 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		160 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
1,2-Ethanediamine	TWA	10 ppm		US. ACGIH Threshold Limit Values (2008)
	TWA PEL	10 ppm	25 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	PEL	10 ppm	25 mg/m3	US. ÓSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	TWA	10 ppm	25 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	AN ESL		25 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		100 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	AN ESL		10 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	REL	10 ppm	25 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	ST ESL		250 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)



	TWA	10 ppm	25 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
Morpholine, 4-ethyl-	REL	5 ppm	23 mg/m3	US. NIOSH: Pocket Guide to Chemical Hazards (2005)
	TWA	5 ppm	23 mg/m3	US. OSHA Table Z-1-A (29 CFR 1910.1000) (1989)
	TWA	5 ppm	23 mg/m3	US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A (06 2008)
	TWA PEL	5 ppm	23 mg/m3	US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants (09 2006)
	PEL	20 ppm	94 mg/m3	US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) (02 2006)
	AN ESL		24 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	TWA	5 ppm		US. ACGIH Threshold Limit Values (2008)
	AN ESL		5.1 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		51 ppb	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)
	ST ESL		240 µg/m3	US. Texas. Effects Screening Levels (Texas Commission on Environmental Quality) (11 2016)

Biological Limit Values

Chemical Identity	Exposure Limit Values	Source
Benzene, methyl- (toluene: Sampling time: End of shift.)	0.03 mg/l (Urine)	ACGIH BEL (03 2013)
Benzene, methyl- (o-Cresol, with hydrolysis: Sampling time: End of shift.)	0.3 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Benzene, methyl- (toluene: Sampling time: Prior to last shift of work week.)	0.02 mg/l (Blood)	ACGIH BEL (03 2013)
2-Propanone (acetone: Sampling time: End of shift.)	25 mg/l (Urine)	ACGIH BEL (03 2015)
Ethanol, 2-butoxy- (Butoxyacetic acid (BAA), with hydrolysis: Sampling time: End of shift.)	200 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)
Ethanol, 2-methoxy- (2- Methoxyacetic acid: Sampling time: End of shift at end of work week.)	1 mg/g (Creatinine in urine)	ACGIH BEL (03 2013)

Appropriate Engineering Controls

No data available.

Individual protection measures, such as personal protective equipment

General information:	Provide easy access to water supply and eye wash facilities. Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If exposure limits have not been established, maintain airborne levels to an acceptable level.
Eye/face protection:	Wear safety glasses with side shields (or goggles).



Skin Protection Hand Protection:	No data available.
Other:	Wear chemical-resistant gloves, footwear, and protective clothing appropriate for the risk of exposure. Contact health and safety professional or manufacturer for specific information.
Respiratory Protection:	In case of inadequate ventilation use suitable respirator. Seek advice from local supervisor.
Hygiene measures:	Avoid contact with eyes. Observe good industrial hygiene practices. When using do not smoke. Do not handle until all safety precautions have been read and understood. Obtain special instructions before use. Wash contaminated clothing before reuse. Avoid contact with skin. Wash hands before breaks and immediately after handling the product.

9. Physical and chemical properties

Appearance

Physical state:	liquid
Form:	Spray Aerosol
Color:	No data available.
Odor:	No data available.
Odor threshold:	No data available.
pH:	No data available.
Melting point/freezing point:	No data available.
Initial boiling point and boiling range:	No data available.
Flash Point:	-104.44 °C
Evaporation rate:	No data available.
Flammability (solid, gas):	No data available.
Upper/lower limit on flammability or explosive	e limits
Flammability limit - upper (%):	No data available.
Flammability limit - lower (%):	No data available.
Explosive limit - upper (%):	No data available.
Explosive limit - lower (%):	No data available.
Vapor pressure:	413.682 - 517.1025 hPa (20 °C) 689.47 - 827.364 hPa (50 °C)
Vapor density:	No data available.
Density:	No data available.
Relative density:	No data available.
Solubility(ies)	
Solubility in water:	No data available.
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	No data available.
Auto-ignition temperature:	No data available.
Decomposition temperature:	No data available.
Viscosity:	No data available.
-	



10. Stability and reactivity

Reactivity:	No data available.
Chemical Stability:	Material is stable under normal conditions.
Possibility of hazardous reactions:	No data available.
Conditions to avoid:	Avoid heat or contamination.
Incompatible Materials:	No data available.
Hazardous Decomposition Products:	No data available.

11. Toxicological information

Information on likely routes of exposure

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Symptoms related to the physical, chemical and toxicological characteristics

Inhalation:	No data available.
Skin Contact:	No data available.
Eye contact:	No data available.
Ingestion:	No data available.

Information on toxicological effects

Acute toxicity (list all possible routes of exposure)

Oral Product:	ATEmix: 17,885.53 mg/kg
Dermal Product:	ATEmix: 11,258.7 mg/kg
Inhalation Product:	ATEmix: 359.28 mg/l ATEmix : 32.66 mg/l

Repeated dose toxicity	
Product:	

No data available.




Specified substance(s):	
Benzene, methyl-	LOAEL (Rat(Female, Male), Oral, 13 Weeks): 1,250 mg/kg (Target Organ(s): Liver, Kidney) Oral Experimental result, Key study NOAEL (Rat(Female, Male), Inhalation): 625 ppm(m) Inhalation Experimental result, Key study
	NOAEL (Rat(Female, Male), Inhalation - vapor): 2,355 mg/l Inhalation
2-Propanone	Experimental result, Key study NOAEL (Rat(Male), Oral, 13 Weeks): 10,000 ppm(m) Oral Experimental result, Key study
Propane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Butane	NOAEL (Rat(Female, Male), Inhalation, >= 28 d): 4,000 ppm(m) Inhalation Experimental result, Key study
	LOAEL (Rat(Female, Male), Inhalation, >= 28 d): 12,000 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Rabbit(Female, Male), Dermal, 90 d): > 150 mg/kg Dermal Experimental result, Key study
	NOAEL (Rat(Female), Oral, 90 d): < 82 mg/kg Oral Experimental result, Key study
	NOAEL (Rat(Female), Inhalation, 2 yr): < 31 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-(2- butoxyethoxy)-	NOAEL (Rat(Female, Male), Oral, 90 d): > 255 mg/kg Oral Experimental result, Supporting study
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	LOAEL (Rat, Oral, 30 d): 94 mg/kg Oral Experimental result, Supporting study
	NOAEL (Rat(Female, Male), Oral, 30 d): 94 mg/kg Oral Experimental result, Supporting study
	NOAEL (Rat, Oral, 30 d): 51 mg/kg Oral Experimental result, Supporting study
	NOAEL (Rat(Female), Inhalation, 5 Weeks): 6 ppm(m) Inhalation Experimental result, Supporting study
Morpholine	LOAEL (Rat(Female), Oral, 56 d): 500 mg/kg Oral Experimental result, Key study
	NOAEL (Rat(Female, Male), Inhalation): 36 ppm(m) Inhalation Experimental result, Key study
	NOAEL (Rat(Female, Male), Inhalation): 50 ppm(m) Inhalation Experimental result, Key study
Ethanol, 2-methoxy-	LOAEL (Rat(Male), Oral, 90 d): 71 mg/kg Oral Experimental result, Key study
	NOAEL (Rabbit(Female, Male), Inhalation, 13 Weeks): 100 ppm(m) Inhalation Experimental result, Key study
	LOAEL (Rat(Female), Inhalation, 13 Weeks): 100 ppm(m) Inhalation Experimental result, Supporting study
1,2-Ethanediamine	NOAEL (Rat(Female, Male), Inhalation, 6 Weeks): 59 ppm(m) Inhalation Experimental result, Key study
	LOAEL (Rat(Female, Male), Oral, 3 Months): 114 mg/kg Oral Experimental result, Key study
Corrosion/Irritation	

Skin Corrosio Product:

No data available.

Specified substance(s):





Benzene, methyl-	in vivo (Rabbit): Irritating Experimental result, Key study
2-Propanone	in vivo (Rabbit): Not irritant Experimental result, Supporting study
Ethanol, 2-butoxy-	in vivo (Rabbit): Irritating Experimental result, Key study
Ethanol, 2-(2- butoxyethoxy)-	in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Not irritant Experimental result, Supporting study in vivo (Rabbit): Slightly irritating Experimental result, Key study in vivo (Rat): classification not possible based on data Experimental result, Supporting study
Morpholine	in vivo (Rabbit): Irritating Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Supporting study in vivo (Rabbit): Corrosive Experimental result, Key study in vivo (Rabbit): Corrosive Experimental result, Supporting study
Ethanol, 2-methoxy-	in vivo (Rabbit): Not irritant Experimental result, Key study
1,2-Ethanediamine	in vivo (Rabbit): Corrosive Experimental result, Key study
Morpholine, 4-ethyl-	Assessment (Various): Corrosive Expert judgment

Serious Eye Damage/Eye Irritation

No data available.
Rabbit, 24 - 72 hrs: Not irritating
Irritating. Rabbit, 24 hrs: Minimum grade of severe eye irritant
Rabbit, 24 - 72 hrs: Irritating
Rabbit, 24 hrs: Moderately irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 48 hrs: Moderately irritating Rabbit, 24 - 72 hrs: Highly irritating Rabbit, 72 hrs: Moderately irritating Rabbit, 48 hrs: Not irritating Rabbit, 24 hrs: Moderately irritating
Corrosive Rabbit, 2 d: 10% Sodium Hydroxide- Category 1; 0.5% Sodium Hydroxide- Slightly irritating to eyes



1,2-Ethanediamine	Rabbit, 24 - 72 hrs: Corrosive		
Morpholine, 4-ethyl-	Corrosive		
Respiratory or Skin Sensitization Product:	No data available.		
Specified substance(s): Benzene, methyl- 2-Propanone Ethanol, 2-butoxy- Ethanol, 2-(2- butoxyethoxy)- Morpholine Ethanol, 2-methoxy- 1,2-Ethanediamine	Skin sensitization:, in vivo (Guinea pig): Non sensitising Skin sensitization:, in vivo (Guinea pig): Non sensitising May cause sensitization by inhalation and skin contact.		
Carcinogenicity Product:	No data available.		
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans:			

No carcinogenic components identified

US. National Toxicology Program (NTP) Report on Carcinogens: No carcinogenic components identified

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050): No carcinogenic components identified

Germ Cell Mutagenicity

In vitro Product:	No data available.	
In vivo Product:	No data available.	
Reproductive toxicity Product:	No data available.	
Specified substance(s): Benzene, methyl- Ethanol, 2-methoxy-	Suspected of damaging fertility or the unborn child. May cause adverse reproductive effects - such as infertility based on animal data.	
Specific Target Organ Toxicity - Single Exposure		
Product: Specified substance(s):	No data available.	
Benzene, methyl- 2-Propanone	Inhalation - vapor: Narcotic effect Category 3 with narcotic effects. Inhalation - vapor: Narcotic effect Category 3 with narcotic effects.	
Specific Target Organ Toxicity - Repeated Exposure Product: No data available. Specified substance(s):		



Benzene, methyl-	Category 2
Aspiration Hazard Product:	No data available.
Specified substance(s): Benzene, methyl-	May be fatal if swallowed and enters airways.
Other effects:	No data available.

12. Ecological information

Ecotoxicity:

Acute hazards to the aquatic environment:

Fish Product:	No data available.
Specified substance(s): Benzene, methyl-	LC 50 (Oncorhynchus kisutch, 96 h): 5.5 mg/l Experimental result, Key study
2-Propanone	LC 50 (Oncorhynchus mykiss, 96 h): 5,540 mg/l Experimental result, Key study
Propane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Butane	LC 50 (Various, 96 h): 147.54 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy-	LC 50 (Oncorhynchus mykiss, 96 h): 1,474 mg/l Experimental result, Key study
Ethanol, 2-(2- butoxyethoxy)-	LC 50 (Goldfish (Carassius auratus), 24 h): 2,700 mg/l Mortality LC 50 (Bluegill (Lepomis macrochirus), 96 h): 1,300 mg/l Mortality LC 50 (Inland silverside (Menidia beryllina), 96 h): 2,000 mg/l Mortality LC 50 (Carp (Leuciscus idus melanotus), 48 h): 1,805 mg/l Mortality LC 50 (Carp (Leuciscus idus melanotus), 48 h): 2,304 mg/l Mortality
Sodium hydroxide (Na(OH))	LC 50 (Western mosquitofish (Gambusia affinis), 96 h): 125 mg/l Mortality LC 50 (Gambusia affinis, 96 h): < 180 mg/l Experimental result, Supporting study
Morpholine	LC 50 (Oncorhynchus mykiss, 96 h): 180 mg/l Experimental result, Key study LC 0 (Vala mugil engeli, 96 h): 100 mg/l Experimental result, Key study LC 50 (Vala mugil engeli, 96 h): 179 mg/l Experimental result, Key study LC 50 (Oncorhynchus mykiss, 96 h): 380 mg/l Experimental result, Key study LC 100 (Vala mugil engeli, 96 h): 320 mg/l Experimental result, Key study
Ethanol, 2-methoxy-	LC 50 (Rainbow trout,donaldson trout (Oncorhynchus mykiss), 96 h): 14,000 - 18,000 mg/l Mortality



1,2-Ethanediamine	LC 50 (Poecilia reticulata, 96 h): 640 mg/l Experimental result, Key study
Aquatic Invertebrates Product:	No data available.
Specified substance(s): Benzene, methyl-	LC 50 (Water flea (Daphnia magna), 48 h): 54.6 - 174.7 mg/l Mortality LC 50 (Ceriodaphnia dubia, 2 d): 3.78 mg/l Experimental result, Key study
2-Propanone	LC 50 (Daphnia pulex, 48 h): 8,800 mg/l Experimental result, Key study
Butane	LC 50 (Daphnia sp., 48 h): 69.43 mg/l QSAR QSAR, Key study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna, 48 h): 1,550 mg/l Experimental result, Key study
Ethanol, 2-(2- butoxyethoxy)-	LC 50 (Water flea (Daphnia magna), 24 h): 2,850 mg/l Mortality ED 0 (Daphnia magna, 48 h): 1,870 mg/l Experimental result, Supporting study LC 100 (Daphnia magna, 24 h): 3,850 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 24 h): 3,200 mg/l Experimental result, Supporting study ED 0 (Daphnia magna, 24 h): 2,333 mg/l Experimental result, Supporting study
Sodium hydroxide (Na(OH))	EC 50 (Water flea (Ceriodaphnia dubia), 48 h): 34.59 - 47.13 mg/l Intoxication
Morpholine	EC 100 (Daphnia magna, 24 h): 260 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 24 h): 101 mg/l Experimental result, Supporting study ED 0 (Daphnia magna, 24 h): 68 mg/l Experimental result, Supporting study EC 50 (Daphnia magna, 48 h): 45 mg/l Experimental result, Key study EC 50 (Water flea (Daphnia magna), 24 h): 112 - 127 mg/l Intoxication
Ethanol, 2-methoxy-	EC 50 (Daphnia magna, 48 h): 27,000 mg/l Experimental result, Key study
1,2-Ethanediamine	EC 50 (Daphnia magna, 48 h): 16.7 mg/l Experimental result, Key study

Chronic hazards to the aquatic environment:

Fish	ו
D	

Product:	No data available.
Specified substance(s): Benzene, methyl-	NOAEL (Oncorhynchus kisutch): 1.39 mg/l Experimental result, Key study LOAEL (Oncorhynchus kisutch): 2.77 mg/l Experimental result, Key study
Ethanol, 2-butoxy-	NOAEL (Danio rerio): > 100 mg/l Experimental result, Key study
1,2-Ethanediamine	NOAEL (Gasterosteus aculeatus): > 10 mg/l Experimental result, Key study
Aquatic Invertebrates Product:	No data available.




Benzene, methyl-	LOAEL (Ceriodaphnia dubia): 2.76 mg/l Experimental result, Key study NOAEL (Ceriodaphnia dubia): 0.74 mg/l Experimental result, Key study
2-Propanone	LOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study NOAEL (Daphnia magna): 2,212 mg/l Experimental result, Key study
Ethanol, 2-butoxy-	EC 50 (Daphnia magna): 297 mg/l Experimental result, Key study EC 10 (Daphnia magna): 134 mg/l Experimental result, Key study
Morpholine	NOAEL (Daphnia magna): 5 mg/l Experimental result, Key study EC 50 (Daphnia magna): 12 mg/l Experimental result, Key study
Ethanol, 2-methoxy-	NOAEL (Daphnia magna): > 500 mg/l Experimental result, Key study
1,2-Ethanediamine	NOAEL (Daphnia magna): 0.16 mg/l Experimental result, Key study
Toxicity to Aquatic Plants Product:	No data available.

Persistence and Degradability

Biodegradation Product:	No data available.
Specified substance(s): Benzene, methyl-	100 % (14 d) Detected in water. Experimental result, Weight of Evidence study 86 % Detected in water. Experimental result, Weight of Evidence study
2-Propanone	90.9 % (28 d) Detected in water. Experimental result, Key study
Propane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Butane	100 % (385.5 h) Detected in water. Experimental result, Key study 50 % (3.19 d) Detected in water. QSAR, Weight of Evidence study
Ethanol, 2-butoxy-	90.4 % Detected in water. Experimental result, Key study
Ethanol, 2-(2- butoxyethoxy)-	14 % Detected in water. Experimental result, Supporting study 60.8 % Detected in water. Experimental result, Supporting study 2 % Detected in water. Experimental result, Supporting study 49.2 % Detected in water. Experimental result, Supporting study 13.1 % Detected in water. Experimental result, Supporting study
Morpholine	80 - 94 % (24 h) Sediment Experimental result, Key study 5.5 % Detected in water. Experimental result, Key study 98 % Detected in water. Experimental result, Supporting study 2 % Detected in water. Experimental result, Key study 17 % Detected in water. Experimental result, Supporting study
Ethanol, 2-methoxy-	82 % (14 d) Detected in water. Experimental result, Supporting study 74 % Detected in water. Experimental result, Key study
1,2-Ethanediamine	88 % Detected in water. Experimental result, Key study
BOD/COD Ratio	

SDS_US - RE1000010423





Product:	No data available.	
Bioaccumulative potential Bioconcentration Factor (BCF) Product: No data available.		
Specified substance(s): Benzene, methyl-	Leuciscus idus, Bioconcentration Factor (BCF): 90 Aquatic sediment Experimental result, Key study	
2-Propanone	Haddock, adult, Bioconcentration Factor (BCF): 0.69 Aquatic sediment Experimental result, Not specified	
Morpholine	Cyprinus carpio, Bioconcentration Factor (BCF): <= 0.65 Aquatic sediment Experimental result, Key study Cyprinus carpio, Bioconcentration Factor (BCF): < 2.8 Aquatic sediment Experimental result, Key study	
Partition Coefficient n-octanol / w Product:	vater (log Kow) No data available.	
Mobility in soil:	No data available.	
Known or predicted distribut	tion to environmental compartments	
Benzene, methyl-	No data available.	
2-Propanone	No data available.	
Propane	No data available.	
Butane	No data available.	
Ethanol, 2-butoxy-	No data available.	
Ethanol, 2-(2-	No data available.	
butoxyethoxy)-		
Quaternary ammonium compounds, benzyl(hydrogenated tallow alkyl)dimethyl, bis(hydrogenated tallow alkyl)dimethylammonium salt with bentonite	No data available.	
Sodium hydroxide (Na(OH))	No data available.	
Morpholine	No data available.	
Quartz (SiO2)	No data available.	
Ethanol, 2-methoxy-	No data available.	
1,2-Ethanediamine	No data available.	
Morpholine, 4-ethyl-	No data available.	
Other adverse effects:	Harmful to aquatic organisms.	
13. Disposal considerations		
Disposal instructions:	Discharge, treatment, or disposal may be subject to national, state, or local laws.	
Contaminated Packaging:	No data available.	



14. Transport information

DOT

Transport Hazard Class(es Class:	UN Proper Shipping Name:	UN 1950 Aerosols, flammable
	Class:	2.1
	Label(s): Packing Group: Marine Pollutant:	– II No
	Environmental Hazards: Marine Pollutant	No No
	Special precautions for user:	Not regulated.
IMC	DG UN Number: UN Proper Shipping Name: Transport Hazard Class(es) Class: Label(s): EmS No.:	UN 1950 Aerosols, flammable 2 -
	Packing Group:	_
	Environmental Hazards: Marine Pollutant	No No
	Special precautions for user:	Not regulated.
IAT	A UN Number: Proper Shipping Name: Transport Hazard Class(es): Class: Label(s):	UN 1950 Aerosols, flammable 2.1 –
	Packing Group:	_
	Environmental Hazards: Marine Pollutant	No No
	Special precautions for user:	Not regulated.

15. Regulatory information

US Federal Regulations TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)



US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

A ha
ey ef
effec

OSHA hazard(s) kidney effects

lung effects immune system effects Cancer

CERCLA Hazardous Substance List (40 CFR 302.4):

Chemical Identity	Reportable quantity
Benzene, methyl-	lbs. 1000
2-Propanone	lbs. 5000
Propane	lbs. 100
Butane	lbs. 100
Sodium hydroxide	lbs. 1000
(Na(OH))	
Morpholine	lbs. 100
1,2-Ethanediamine	lbs. 5000
Morpholine, 4-ethyl-	lbs. 100

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Fire Hazard Immediate (Acute) Health Hazards Delayed (Chronic) Health Hazard Flammable aerosol Skin Corrosion/Irritation Serious Eye Damage/Eye Irritation Toxic to reproduction Aspiration Hazard

SARA 302 Extremely Hazardous Substance

	<u>Reportable</u>	
Chemical Identity	quantity	-
2-Propanone		
1,2-Ethanediamine	lbs. 5000	

Threshold Planning Quantity

lbs. 10000

SARA 304 Emergency Release Notification Chemical Identity Reportable quantity

Chemical Iden	tity	Reportable qua
Benzene, meth	yl-	lbs. 1000
2-Propanone		lbs. 5000
Propane		lbs. 100
Butane		lbs. 100
Ethanol, 2-buto	xy-	
Ethanol,	2-(2-	
butoxyethoxy)-		
Sodium	hydroxide	lbs. 1000
(Na(OH))		
Morpholine		lbs. 100
Ethanol, 2-metl	noxy-	
1,2-Ethanedian	nine	lbs. 5000
Morpholine, 4-e	ethyl-	lbs. 100



SARA 311/312 Hazardous Chemical		
Chemical Identity	Threshold Plannir	ng Quantity
1,2-Ethanediamine	lbs	
Benzene, methyl-	10000 lbs	
2-Propanone	10000 lbs	
Propane	10000 lbs	
Butane	10000 lbs	
Ethanol, 2-butoxy-	10000 lbs	
Ethanol, 2-(2-	10000 lbs	
butoxyethoxy)-		
Quaternary ammonium	10000 lbs	
compounds,		
benzyl(hydrogenated		
tallow alkyl)dimethyl,		
bis(hydrogenated tallow		
alkyl)dimethylammonium		
salt with bentonite		
Sodium hydroxide	10000 lbs	
(Na(OH))		
Morpholine	10000 lbs	
Quartz (SiO2)	10000 lbs	
Ethanol, 2-methoxy-	10000 lbs	
Morpholine, 4-ethyl-	10000 lbs	
SARA 313 (TRI Reporting)		
	<u>Reporting</u>	Reporting threshold for
	threshold for	manufacturing and
Chemical Identity	other users	processing
Benzene, methyl-	lbs	lbs.
Ethanol, 2-butoxy-	N230 lbs	N230 lbs.
Ethanol, 2-(2-	N230 lbs	N230 lbs.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130): Clean Water Act Section 311 Hazardous Substances (40 CFR 117.3) US State Regulations

US. California Proposition 65

butoxyethoxy)-

This product contains chemical(s) known to the State of California to cause cancer and/or to cause birth defects or other reproductive harm.

Benzene, methyl-	Developmental toxin. 03 2008
Quartz (SiO2)	Carcinogenic. 05 2011
Ethanol, 2-methoxy-	Developmental toxin. 03 2008
Ethanol, 2-methoxy-	Male reproductive toxin. 03 2008

US. New Jersey Worker and Community Right-to-Know Act

Chemical Identity

Benzene, methyl-2-Propanone Propane Butane Ethanol, 2-butoxy-Ethanol, 2-(2-butoxyethoxy)-



US. Massachusetts RTK - Substance List

Chemical Identity Quartz (SiO2) 1,2-Ethanediamine

US. Pennsylvania RTK - Hazardous Substances

Chemical Identity

Benzene, methyl-2-Propanone Propane Butane Ethanol, 2-butoxy-Ethanol, 2-(2-butoxyethoxy)-9-Octadecenoic acid (9Z)-

US. Rhode Island RTK

No ingredient regulated by RI Right-to-Know Law present.

International regulations

Montreal protocol

Not applicable

Stockholm convention

Not applicable

Rotterdam convention

Not applicable

Kyoto protocol

Not applicable



Inventory Status: Australia AICS:

Australia AICS:	On or in compliance with the inventory
Canada DSL Inventory List:	On or in compliance with the inventory
EINECS, ELINCS or NLP:	Not in compliance with the inventory.
Japan (ENCS) List:	Not in compliance with the inventory.
China Inv. Existing Chemical Substances:	On or in compliance with the inventory
Korea Existing Chemicals Inv. (KECI):	Not in compliance with the inventory.
Canada NDSL Inventory:	Not in compliance with the inventory.
Philippines PICCS:	Not in compliance with the inventory.
US TSCA Inventory:	On or in compliance with the inventory
New Zealand Inventory of Chemicals:	On or in compliance with the inventory
Japan ISHL Listing:	Not in compliance with the inventory.
Japan Pharmacopoeia Listing:	Not in compliance with the inventory.
Mexico INSQ:	Not in compliance with the inventory.
Ontario Inventory:	On or in compliance with the inventory
Taiwan Chemical Substance Inventory:	On or in compliance with the inventory

16.Other information, including date of preparation or last revision

Issue Date:	04/15/2019
Revision Information:	No data available.
Version #:	1.0
Further Information:	No data available.
Disclaimer:	This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.