# Camie

# SAFETY DATA SHEET

#### 1. Identification

Product number 1000002351

Product identifier 12.75 OZ 980 URETHANE RLS AGENT LT 12PK

Company information Camie-Campbell, Inc. 1005 S. Westgate Drive

Addison, IL 60101 United States

www.camie.com

**Company phone** General Assistance 1-800-325-9572

Emergency telephone US
Emergency telephone outside

1-866-836-8855 1-952-852-4646

US

Version # 01

Recommended use Lubricant
Recommended restrictions None known.

# 2. Hazard(s) identification

Physical hazardsFlammable aerosolsCategory 1Health hazardsSkin corrosion/irritationCategory 2Reproductive toxicity (fertility)Category 2

Acproductive toxicity (tertinity)

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated

exposure

Category 2
Category 1

Category 2

Aspiration hazard Category 1

Environmental hazards Hazardous to the aquatic environment, acute Category 2

hazard

.

Hazardous to the aquatic environment, long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

**Hazard statement** Extremely flammable aerosol. May be fatal if swallowed and enters airways. Causes skin irritation.

May cause drowsiness or dizziness. Suspected of damaging fertility. May cause damage to organs through prolonged or repeated exposure. Toxic to aquatic life. Toxic to aquatic life with

long lasting effects.

**Precautionary statement** 

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective

clothing/eye protection/face protection.

**Response** If swallowed: Immediately call a poison center/doctor. If on skin: Wash with plenty of water. If

inhaled: Remove person to fresh air and keep comfortable for breathing. If exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Specific treatment (see this label). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention.

Take off contaminated clothing and wash before reuse. Collect spillage.

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up. Protect from

sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** 

Hazard(s) not otherwise classified (HNOC)

Dispose of contents/container in accordance with local/regional/national/international regulations.

None known.

Supplemental information

92.75% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 45.11% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Butane		106-97-8	20 - 40
n-Hexane		110-54-3	20 - 40
2-Methylpentane		107-83-5	10 - 20
Propane		74-98-6	10 - 20
3-Methylpentane		96-14-0	2.5 - 10
2,2-Dimethylbutane		75-83-2	1 - 2.5
2,3-Dimethylbutane		79-29-8	1 - 2.5
Polydimethylsiloxane		63148-62-9	1 - 2.5

<sup>\*</sup>Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

#### 4. First-aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delayed

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of eyes and mucous membranes. Irritation of nose and throat. Aspiration may cause pulmonary edema and

pneumonitis. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic

Indication of immediate medical attention and special

treatment needed **General information**  Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Powder. Foam. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment

and precautions for firefighters

Fire-fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Use standard firefighting procedures and consider the hazards of other involved materials. Move Specific methods

containers from fire area if you can do so without risk. In the event of fire and/or explosion do not

breathe fumes.

Extremely flammable aerosol. General fire hazards

#### 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Prevent entry into waterways, sewer, basements or confined areas. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

## 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Do not breathe gas. Avoid contact with eyes, skin, and clothing. Use only in well-ventilated areas. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 3 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Refrigeration recommended. Store away from incompatible materials (see Section 10 of the SDS).

Value

# 8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)
Components	Type

n-Hexane (CAS 110-54-3)	PEL	1800 mg/m3	
		500 ppm	
Propane (CAS 74-98-6)	PEL	1800 mg/m3	
		1000 ppm	
<b>US. ACGIH Threshold Limit Value</b>	s		
Components	Туре	Value	
2,2-Dimethylbutane (CAS 75-83-2)	STEL	1000 ppm	
	TWA	500 ppm	
2,3-Dimethylbutane (CAS 79-29-8)	STEL	1000 ppm	
	TWA	500 ppm	
2-Methylpentane (CAS 107-83-5)	STEL	1000 ppm	
·	TWA	500 ppm	
3-Methylpentane (CAS 96-14-0)	STEL	1000 ppm	
	TWA	500 ppm	
Butane (CAS 106-97-8)	STEL	1000 ppm	
n-Hexane (CAS 110-54-3)	TWA	50 ppm	
US. NIOSH: Pocket Guide to Cher	nical Hazards		
Components	Туре	Value	
Butane (CAS 106-97-8)	TWA	1900 mg/m3	

## US. NIOSH: Pocket Guide to Chemical Hazards

Components	Туре	Value	
		800 ppm	
n-Hexane (CAS 110-54-3)	TWA	180 mg/m3	
		50 ppm	
Propane (CAS 74-98-6)	TWA	1800 mg/m3	
		1000 ppm	

#### **Biological limit values**

Components	Value	Determinant	Specimen	Sampling Time
n-Hexane (CAS 110-54-3)	0.4 mg/l	2,5-Hexanedio n, without hydrolysis	Urine	*

<sup>\* -</sup> For sampling details, please see the source document.

#### **Exposure guidelines**

US - California OELs: Skin designation

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

**US ACGIH Threshold Limit Values: Skin designation** 

n-Hexane (CAS 110-54-3) Can be absorbed through the skin.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.

#### Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Hand protection Wear appropriate chemical resistant gloves.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Skin protection

Respiratory protection If permissible levels are exceeded use NIOSH mechanical filter / organic vapor cartridge or an

air-supplied respirator.

Wear appropriate thermal protective clothing, when necessary. Thermal hazards

General hygiene considerations

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

## 9. Physical and chemical properties

#### **Appearance**

Gas. **Physical state** Aerosol **Form** Color Not available. Odor Not available. **Odor threshold** Not available. Not available. Ha Melting point/freezing point Not available.

Initial boiling point and boiling

range

154.33 °F (67.96 °C) estimated

Flash point -156.0 °F (-104.4 °C) Propellent estimated

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower Not available.

(%)

Product name: 12.75 OZ 980 URETHANE RLS AGENT LT 12PK

Flammability limit - upper

(%)

7.7 % estimated

Explosive limit - lower (%)

Not available. Explosive limit - upper (%) Not available.

Vapor pressure 35.21 psig @70F estimated

Vapor density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

**Auto-ignition temperature** 496.4 °F (258 °C) estimated

**Decomposition temperature** Not available. **Viscosity** Not available.

Other information

Specific gravity 0.594 estimated

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. Chemical stability Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Nitrates. Fluorine. Chlorine. No hazardous decomposition products are known. Hazardous decomposition

products

# 11. Toxicological information

# Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious

chemical pneumonia.

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting. Narcotic effects.

Skin contact Causes skin irritation.

Direct contact with eyes may cause temporary irritation. Eye contact

Symptoms related to the physical, chemical and toxicological characteristics May cause drowsiness and dizziness. Headache. Nausea, vomiting. Irritation of nose and throat.

Aspiration may cause pulmonary edema and pneumonitis. Irritation of eyes and mucous

membranes. Skin irritation. May cause redness and pain.

#### Information on toxicological effects

May be fatal if swallowed and enters airways. Narcotic effects. **Acute toxicity** 

**Product Species Test Results** 

## 12.75 OZ 980 URETHANE RLS AGENT LT 12PK (CAS Mixture)

**Acute** Dermal

**LD50** Rabbit 6409.9595 mg/kg, 4 Hours estimated

16.9541 ml/kg, 4 Hours estimated

Rat 7837.5752 mg/kg estimated

Inhalation

LC100 Cat 199.5123 % estimated

LC50 Mouse 2742.1858 mg/l, 120 Minutes estimated

> 115.2738 %, 120 Minutes estimated 35.4689 mm/l, 2 Hours estimated

Product name: 12.75 OZ 980 URETHANE RLS AGENT LT 12PK

SDS US Product #: 1000002351 Version #: 01 Issue date: 11-25-2014

Product	Species	Test Results
	Rat	28869.4297 ppm, 4 Hours estimated
		16954.0684 ppm, 24 Hours estimated
		1458.6566 mg/l/4h estimated
		104.2808 mg/l estimated
Oral		
LD50	Rat	292.3977 g/kg estimated
		81.3795 ml/kg estimated
	Wistar rat	166.1499 g/kg estimated
Components	Species	Test Results
utane (CAS 106-97-8)		
Acute		
Inhalation		
LC50	Mouse	1237 mg/l, 120 Minutes
		52 %, 120 Minutes
	Rat	1355 mg/l
-Hexane (CAS 110-54-3)		
Acute		
Dermal	D. I.I.Y	
LD50	Rabbit	> 2000 mg/kg, 4 Hours
		> 5 ml/kg, 4 Hours
Inhalation	Dot	> 5000 ppm 24 Hours
LC50	Rat	> 5000 ppm, 24 Hours
		> 31.86 mg/l
		73860 ppm, 4 Hours
Oral	Det	0.41/1
LD50	Rat	24 ml/kg
		24 g/kg
	Wistar rat	49 g/kg
ropane (CAS 74-98-6)		
Acute		
Inhalation LC50	Mouse	1237 mg/l, 120 Minutes
LOJU	Mode	_
	Det	52 %, 120 Minutes
	Rat	1355 mg/l
		658 mg/l/4h

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

**Respiratory sensitization** Not available.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Reproductive toxicity Suspected of damaging fertility.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure. Respiratory system.

Central nervous system. Eyes. Skin. Peripheral nervous system.

**Aspiration hazard** May be fatal if swallowed and enters airways.

**Chronic effects** May cause damage to organs through prolonged or repeated exposure.

## 12. Ecological information

**Ecotoxicity** Toxic to aquatic life with long lasting effects.

Product		Species	Test Results
12.75 OZ 980 URETH	IANE RLS AGENT L	T 12PK (CAS Mixture)	
Aquatic			
Crustacea	EC50	Daphnia	11628.8828 mg/L, 48 Hours estimated
Fish	LC50	Fish	7.4272 mg/L, 96 Hours estimated
Components		Species	Test Results
n-Hexane (CAS 110-5	54-3)		
Aquatic			
Fish	LC50	Fathead minnow (Pimephales promelas)	2.101 - 2.981 mg/l, 96 hours
Polydimethylsiloxane	(CAS 63148-62-9)		
Aquatic			
Fish	LC50	Channel catfish (Ictalurus punctatus)	2.36 - 4.15 mg/l, 96 hours

<sup>\*</sup> Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential No data available.

Partition coefficient n-octanol / water (log Kow)

2,2-Dimethylbutane	3.82
2,3-Dimethylbutane	3.42
2-Methylpentane	3.74
3-Methylpentane	3.6
Butane	2.89
n-Hexane	3.9
Propane	2.36

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

#### 13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents

under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international

regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

**Contaminated packaging** Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Do not re-use empty containers.

#### 14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, flammable

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) None

Packing group Not applicable.

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Special provisions Packaging exceptions 306 Packaging non bulk None Packaging bulk None

This product meets the exception requirements of section 173.306 as a limited quantity and may be shipped as a limited quantity. Until 12/31/2020, the "Consumer Commodity - ORM-D" marking may still be used in place of the new limited quantity diamond mark for packages of UN 1950 Aerosols. Limited quantities require the limited quantity diamond mark on cartons after 12/31/20 and may be used now in place of the "Consumer Commodity ORM-D" marking and both may be displayed concurrently.

#### IATA

UN1950 **UN** number

Aerosols, flammable **UN proper shipping name** 

Transport hazard class(es)

2.1 Class Subsidiary risk Label(s) None

Packing group Not applicable.

**Environmental hazards** Yes 10L **ERG Code** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

Other information

Passenger and cargo

aircraft

Allowed.

Allowed. Cargo aircraft only **Packaging Exceptions** LTD QTY

**IMDG** 

**UN** number UN1950 **AEROSOLS UN** proper shipping name

Transport hazard class(es)

Class 2.1 Subsidiary risk None Label(s)

Packing group Not applicable.

**Environmental hazards** 

Marine pollutant Yes F-D, S-U **EmS** 

Special precautions for user Read safety instructions, SDS and emergency procedures before handling. Read safety

instructions, SDS and emergency procedures before handling.

LTD QTY **Packaging Exceptions** Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78 and

the IBC Code

DOT



## IATA; IMDG



#### Marine pollutant



General information IMDG Regulated Marine Pollutant.

# 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

#### TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)** 

n-Hexane (CAS 110-54-3) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

## Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

# SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

## SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
n-Hexane	110-54-3	20 - 40	_

#### Other federal regulations

## Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

n-Hexane (CAS 110-54-3)

## Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Butane (CAS 106-97-8) Propane (CAS 74-98-6)

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

#### **US. Massachusetts RTK - Substance List**

2,2-Dimethylbutane (CAS 75-83-2)

2,3-Dimethylbutane (CAS 79-29-8)

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

# US. New Jersey Worker and Community Right-to-Know Act

2,2-Dimethylbutane (CAS 75-83-2)

2,3-Dimethylbutane (CAS 79-29-8)

2-Methylpentane (CAS 107-83-5)

Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

### US. Pennsylvania Worker and Community Right-to-Know Law

2,2-Dimethylbutane (CAS 75-83-2)

2,3-Dimethylbutane (CAS 79-29-8)

2-Methylpentane (CAS 107-83-5)

3-Methylpentane (CAS 96-14-0)

Butane (CAS 106-97-8)

n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

#### **US. Rhode Island RTK**

Butane (CAS 106-97-8) n-Hexane (CAS 110-54-3)

Propane (CAS 74-98-6)

#### **US. California Proposition 65**

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date 11-25-2014

Version # 01

United States & Puerto Rico

**Disclaimer** The information provided in this Safety Data Sheet is correct to the best of our knowledge,

Toxic Substances Control Act (TSCA) Inventory

information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other

materials or in any process, unless specified in the text.

Product name: 12.75 OZ 980 URETHANE RLS AGENT LT 12PK Product #: 1000002351 Version #: 01 Issue date: 11-25-2014 Yes

**Revision Information** 

Product and Company Identification: Product Uses

First-aid measures: Most important symptoms/effects, acute and delayed

Fire-fighting measures: Specific methods

Accidental release measures: Personal precautions, protective equipment and emergency

procedures

Accidental release measures: Environmental precautions Handling and storage: Precautions for safe handling

Exposure controls/personal protection: Appropriate engineering controls

Physical & Chemical Properties: Multiple Properties

Toxicological information: Ingestion Toxicological information: Inhalation

Toxicological information: Specific target organ toxicity - single exposure

Toxicological information: Symptoms related to the physical, chemical and toxicological

characteristics

Regulatory Information: United States

GHS: Classification